



Quality meets Innovation

Accessories Catalogue



Accessories Catalogue

HBS Welding Systems GmbH
Felix-Wankel-Strasse 18
85221 Dachau
GERMANY

Phone **+49 8131 511-0**
E-Mail **sales@hbswelding.systems**
Web **www.hbswelding.systems**

Accessories Catalogue

Transmission and duplication of this document, dissemination and notification of the contents are not permitted unless expressly approved.

Pictorial representations may differ from the original.

All rights, errors and technical amendments reserved.




© HBS Bolzenschweiss-Systeme GmbH & Co. KG






Table of Contents

1	Manual stud welding – CD / tip ignition	6
	Equipment for C 06-3	8
	Equipment for C 08 / CA 08	12
	Welding gun accessories for C 06-3 / C 08 / CA 08	16
	Leg assemblies – details for C 06-3 / C 08 / CA 08	17
	Equipment for CI 03	18
	Accessories for ACCU-TWIN	20
	Accessories for Pegasar 500 Accu	26
2	Manual stud welding – drawn arc with ceramic ferrule	28
	Equipment for A 12	30
	Equipment for A 12-FL	32
	Welding gun accessories for A 12 / A 12-FL	34
	Leg assemblies – details for A 12 / A 12-FL	35
	Equipment for A 16	36
	Equipment for A 22	42
	Equipment for A 25	46
	Welding gun accessories for A 16 / A 22 / A 25 (RD / DD / PD / UD / ID)	50
	Welding gun accessories for A 16 / A 22 / A 25 (concrete anchors SD)	52
	Leg assemblies – details for A 16 / A 22 / A 25	55
3	Manual stud welding – drawn arc with shielding gas	58
	Equipment for A 12	60
	Equipment for A 12-FL	62
	Equipment for A 16	64
	Welding gun accessories for A 12 / A 12-FL / A 16	66
	Leg assemblies – details for A 12 / A 12-FL / A 16	67
4	Manual stud welding – drawn arc ISO	68
	Equipment for A 12-FL / AI 06	70
	Equipment for A 12	72
	Leg assemblies – details for A 12 / A 12-FL / AI 06	74



5	Manual stud welding – SC (short cycle)	76
	Equipment for CA 08	78
	Equipment for A 12	80
	Welding gun accessories for CA 08 / A 12	82
	Leg assemblies – details for CA 08 / A 12	83
6	Manual nut welding – MARC 1	84
	Equipment for AM 12 A	86
7	Automatic stud welding – PAH-1 / components / CNC	88
	Equipment for PAH-1	90
	Equipment for KAH 412	102
	Pneumatic ground clamps	117
	T-slot blocks / Zero-point stop pins	120
	PBZ (pneumatic single feed unit)	122
	Further components	124
	Accessories for MPW	128
8	Ground / extension cables	130
	Coupling types	132
	Extension cables and adaptors	133
	Ground cables	134
9	Other accessories	136
	Bending device	138
	Torque bending test device	138
	Automatic center punch	138
	Socket wrench	139
	Quickboy / Bench mounting unit	139
	Surface and component protection	140
	Notes	141

Equipment for C 06-3	Page
	8 - 11
Equipment for C 08 / CA 08	Page
	12 - 15
Equipment for C 08-FS	Page
	<?> - <?>
Welding gun accessories for C 06-3 / C 08-FS / C 08 / CA 08	Page
	16

Leg assemblies – Detail views for C 06-3 / C 08--FS / C 08 / CA 08	Page
	17
Equipment for CI 03	Page
	18 - 19
Accessories for ACCU-TWIN	Page
	24 - 29
Accessories for Pegasar 500 accu	Page
	26 - 27

Equipment				Foot ring with feet (Standard equipment)	Foot ring TK 38 with feet		
Chucks				universal application on flat surfaces (pitch circle dia. 34 mm)  Foot ring: 80-40-373 Foot: 80-40-049 assembled: 	larger pitch circle dia. (38 mm) for higher stability when placing on the workpiece  Foot ring 80-40-521 Foot: 80-40-077 assembled: 		
	for CD threaded studs / pins		Welding element dia.	Order No.	Length from min.	to max.	Length from min.
dia. 2 mm			82-50-002	6 mm	40 mm	6 mm	40 mm
dia. 2.5 mm			82-50-025				
dia. 3 mm			82-50-003				
dia. 4 mm			82-50-004				
dia. 5 mm			82-50-005	X	X		
dia. 6 mm			82-50-006				
dia. 7.1 mm			82-50-071				
dia. 8 mm	82-50-008						
dia. 10 mm	82-50-009						
for CD studs with internal thread		Welding element dia.	Order No.	Length from min.	to max.	Length from min.	to max.
		dia. 5 mm	82-50-905	6 mm	35 mm	6 mm	35 mm
		dia. 6 mm	82-50-906				
		dia. 7.1 mm	82-50-971	X	X		
dia. 8 mm	82-50-908						
for ground clips		Welding element	Order No.	✓		✓	
		b = 6.3 mm	82-50-050				
for CD ISO nails		Welding element dia.	Order No.	Length from min.	to max.	Length from min.	to max.
		dia. 2 mm	82-50-020	20 mm	105 mm	20 mm	105 mm
		dia. 3 mm	82-50-030				
		dia. 2.7 mm	82-50-027				


Distance ring with foot ring and feet		Offset chuck adaptor with foot ring and feet		usable with stud welding unit:		
for longer welding elements and welding elements with dia. 10 mm		for welding in corners (minimum distance 9 mm)				
 Foot ring: 80-40-373 Distance ring 92-40-010 with screws Foot: 80-40-049 <u>assembled:</u> 		 Offset chuck adaptor: 82-40-011 Foot ring: 80-40-373 Foot: 80-40-049 <u>assembled:</u> 		CDI 502 with ground cable 92-40-154 	Pegasar 500 accu with ground cable 92-40-154 	Pegasar 500 accu Insulation with ground cable 92-40-154 
Length from min. to max.		Length from min. to max.				
25 mm to 55 mm		6 mm to 40 mm		✓	✓	✗
✗		✗		✗	✗	
Length from min. to max.		Length from min. to max.				
25 mm to 50 mm		6 mm to 35 mm		✓	✓	✗
✗		✗				
✗		✗		✓	✓	✗
✗		✗		✓	✗	✓

Equipment			Noise damping tube	Centering tube																																
Chucks			for reducing noise level during welding, for welding elements up to dia. 5 mm  Noise damping tube: 82-40-016 assembled:  Ø 35 mm	for welding in templates and for protection against welding sparks  Centering tube: 80-40-513 assembled:  Ø 30 mm																																
	for CD threaded studs / pins		<table><tr><td>Welding element dia.</td><td>Order No.</td></tr><tr><td>dia. 2 mm</td><td>82-50-002</td></tr><tr><td>dia. 2.5 mm</td><td>82-50-025</td></tr><tr><td>dia. 3 mm</td><td>82-50-003</td></tr><tr><td>dia. 4 mm</td><td>82-50-004</td></tr><tr><td>dia. 5 mm</td><td>82-50-005</td></tr><tr><td>dia. 6 mm</td><td>82-50-006</td></tr><tr><td>dia. 7.1 mm</td><td>82-50-071</td></tr><tr><td>dia. 8 mm</td><td>82-50-008</td></tr><tr><td>dia. 10 mm</td><td>82-50-009</td></tr></table>	Welding element dia.	Order No.	dia. 2 mm	82-50-002	dia. 2.5 mm	82-50-025	dia. 3 mm	82-50-003	dia. 4 mm	82-50-004	dia. 5 mm	82-50-005	dia. 6 mm	82-50-006	dia. 7.1 mm	82-50-071	dia. 8 mm	82-50-008	dia. 10 mm	82-50-009	<table><tr><td colspan="2">Length</td></tr><tr><td>from min.</td><td>to max.</td></tr><tr><td>6 mm</td><td>40 mm</td></tr></table>	Length		from min.	to max.	6 mm	40 mm	<table><tr><td colspan="2">Length</td></tr><tr><td>from min.</td><td>to max.</td></tr><tr><td>6 mm</td><td>40 mm</td></tr></table>	Length		from min.	to max.	6 mm
Welding element dia.		Order No.																																		
dia. 2 mm		82-50-002																																		
dia. 2.5 mm		82-50-025																																		
dia. 3 mm		82-50-003																																		
dia. 4 mm		82-50-004																																		
dia. 5 mm		82-50-005																																		
dia. 6 mm		82-50-006																																		
dia. 7.1 mm	82-50-071																																			
dia. 8 mm	82-50-008																																			
dia. 10 mm	82-50-009																																			
Length																																				
from min.	to max.																																			
6 mm	40 mm																																			
Length																																				
from min.	to max.																																			
6 mm	40 mm																																			
for CD studs with internal thread		<table><tr><td>Welding element dia.</td><td>Order No.</td></tr><tr><td>dia. 5 mm</td><td>82-50-905</td></tr><tr><td>dia. 6 mm</td><td>82-50-906</td></tr><tr><td>dia. 7.1 mm</td><td>82-50-971</td></tr><tr><td>dia. 8 mm</td><td>82-50-908</td></tr></table>	Welding element dia.	Order No.	dia. 5 mm	82-50-905	dia. 6 mm	82-50-906	dia. 7.1 mm	82-50-971	dia. 8 mm	82-50-908	<table><tr><td colspan="2">Length</td></tr><tr><td>from min.</td><td>to max.</td></tr><tr><td>6 mm</td><td>35 mm</td></tr></table>	Length		from min.	to max.	6 mm	35 mm	<table><tr><td colspan="2">Length</td></tr><tr><td>from min.</td><td>to max.</td></tr><tr><td>6 mm</td><td>35 mm</td></tr></table>	Length		from min.	to max.	6 mm	35 mm										
	Welding element dia.	Order No.																																		
	dia. 5 mm	82-50-905																																		
	dia. 6 mm	82-50-906																																		
dia. 7.1 mm	82-50-971																																			
dia. 8 mm	82-50-908																																			
Length																																				
from min.	to max.																																			
6 mm	35 mm																																			
Length																																				
from min.	to max.																																			
6 mm	35 mm																																			
for ground clips		<table><tr><td>Welding element</td><td>Order No.</td></tr><tr><td>b = 6.3 mm</td><td>82-50-050</td></tr></table>	Welding element	Order No.	b = 6.3 mm	82-50-050																														
	Welding element	Order No.																																		
b = 6.3 mm	82-50-050																																			
for CD ISO nails		<table><tr><td>Welding element dia.</td><td>Order No.</td></tr><tr><td>dia. 2 mm</td><td>82-50-020</td></tr><tr><td>dia. 3 mm</td><td>82-50-030</td></tr><tr><td>dia. 2.7 mm</td><td>82-50-027</td></tr></table>	Welding element dia.	Order No.	dia. 2 mm	82-50-020	dia. 3 mm	82-50-030	dia. 2.7 mm	82-50-027	<table><tr><td colspan="2">Length</td></tr><tr><td>from min.</td><td>to max.</td></tr><tr><td>20 mm</td><td>105 mm</td></tr></table>	Length		from min.	to max.	20 mm	105 mm	<table><tr><td colspan="2">Length</td></tr><tr><td>from min.</td><td>to max.</td></tr><tr><td>20 mm</td><td>105 mm</td></tr></table>	Length		from min.	to max.	20 mm	105 mm												
	Welding element dia.	Order No.																																		
	dia. 2 mm	82-50-020																																		
	dia. 3 mm	82-50-030																																		
dia. 2.7 mm	82-50-027																																			
Length																																				
from min.	to max.																																			
20 mm	105 mm																																			
Length																																				
from min.	to max.																																			
20 mm	105 mm																																			

Centering device	Leg assembly PSI-2	usable with stud welding unit:		
for exact positioning in templates by adjusting the concentricity of the chuck to the centering device, chuck extension necessary Centering tube Ø 20 mm: 80-40-082 Ø 26 mm: 80-40-086 Ø 30 mm: 80-40-083 Centering disc Ø 20 mm: 80-40-092 Ø 26 mm: 80-40-096 Ø 30 mm: 80-40-093 Cylindrical pin 80-10-092 Foot ring TK 38 80-40-521 Chuck extension 80-40-081 Centering device: Ø 20 mm: 92-40-111 / Ø 26 mm: 92-40-117 / Ø 30 mm: 92-40-119 assembled: 	für longer ISO nails and welding elements Foot piece with plastic insert 80-40-127 Clamp plate 80-40-126 Tripod leg 80-40-130 Foot 80-40-306 Foot ring 80-40-373 leg assembly PSI-2 92-40-043 (ISO leg assembly, 3-point rest) assembled: 	usable with stud welding unit: CDI 502 with ground cable 92-40-154 Pegasar 500 accu with ground cable 92-40-154 Pegasar 500 accu Insulation with ground cable 92-40-154   		
Length from min. to max.	Length from min. to max.			
6 mm 40 mm	6 mm ⁵⁾ 200 mm ⁵⁾	✓	✓	✗
✗	✗	✗	✗	
✗	Length from min. to max. 6 mm ⁵⁾ 200 mm ⁵⁾	✓	✓	✗
✗	✗			
✗	✗	✓	✓	✗
✗	Length from min. to max. 20 mm ⁵⁾ / 135 mm ⁶⁾ 135 mm ⁵⁾ / 280 mm ⁶⁾	✓	✗	✓

⁵⁾ when used without plastic insert

⁶⁾ when used with plastic insert

Equipment				Foot ring with feet (Standard equipment)	Foot ring TK 38 with feet
Chucks				universal application on flat surfaces (pitch circle dia. 34 mm)	larger pitch circle dia. (38 mm) for higher stability when placing on the workpiece
				 Foot ring: 80-40-373 Foot: 80-40-049 <u>assembled:</u> 	 Foot ring 80-40-521 Foot: 80-40-077 <u>assembled:</u> 
for CD threaded studs / pins		Welding element dia.	Order No.	Length from min. to max.	Length from min. to max.
		dia. 2 mm	82-50-002	6 mm ¹⁾ / 16 mm ²⁾	30 mm ¹⁾ / 40 mm ²⁾
		dia. 2.5 mm	82-50-025		
		dia. 3 mm	82-50-003		
		dia. 4 mm	82-50-004		
		dia. 5 mm	82-50-005		
		dia. 6 mm	82-50-006		
		dia. 7.1 mm	82-50-071		
		dia. 8 mm	82-50-008	X	X
		dia. 10 mm	82-50-009		
for CD studs with internal thread		Welding element dia.	Order No.	Length from min. to max.	Length from min. to max.
		dia. 5 mm	82-50-905	6 mm	30 mm
		dia. 6 mm	82-50-906		
		dia. 7.1 mm	82-50-971		
		dia. 8 mm	82-50-908		
for ground clips		Welding element	Order No.	✓	✓
		b = 6.3 mm	82-50-050		
for CD ISO nails		Welding element dia.	Order No.	Length from min. to max.	Length from min. to max.
		dia. 2 mm	82-50-020	20 mm	20 mm
		dia. 3 mm	82-50-030		
		dia. 2.7 mm	82-50-027		

¹⁾ with standard stop pin

²⁾ additional stop pin 80-90-710 necessary

Distance ring with foot ring and feet		Offset chuck adaptor with foot ring and feet		usable with stud welding unit:		
for longer welding elements and welding elements with dia. 10 mm		for welding in corners (minimum distance 9 mm)				
 Foot ring: 80-40-373 Distance ring 92-40-010 with screws Foot: 80-40-049 <u>assembled:</u> 		 Offset chuck adaptor: 82-40-011 Foot ring: 80-40-373 Foot: 80-40-049 <u>assembled:</u> 		CDI 1502 with ground cable 92-40-095 	CDI 2302 with ground cable 92-40-095 	CDI 3102 with ground cable 92-40-095 
Length from min. to max.		Length from min. to max.				
15 mm ¹⁾ 25 mm ²⁾ 45 mm ¹⁾ / 55 mm ²⁾³⁾		6 mm 40 mm		✓	✓	✓
15 mm 30 mm		✗		✗	(✓)	✓
Length from min. to max.		Length from min. to max.				
25 mm 45 mm		6 mm 35 mm		✓	✓	✓
✗		✗		✓	✓	✗
✗		✗		✓	✗	✗

³⁾ stop pin 80-90-710 included in delivery of distance ring 92-40-010

Equipment				Noise damping tube	Centering tube
Chucks				for reducing noise level during welding, for welding elements up to dia. 5 mm	for welding in templates and for protection against welding sparks
				Noise damping tube: 82-40-016	Centering tube: 80-40-513
				assembled: 	assembled:
for CD threaded studs / nails		Welding element dia.	Order No.	Length from min. to max.	Length from min. to max.
		dia. 2 mm	82-50-002	6 mm ¹⁾ / 16 mm ²⁾	30 mm ¹⁾ / 40 mm ²⁾
		dia. 2.5 mm	82-50-025		
		dia. 3 mm	82-50-003		
		dia. 4 mm	82-50-004		
		dia. 5 mm	82-50-005	X	X
		dia. 6 mm	82-50-006		
		dia. 7.1 mm	82-50-071	X	X
		dia. 8 mm	82-50-008		
for CD studs with internal thread		Welding element dia.	Order No.	Length from min. to max.	Length from min. to max.
		dia. 5 mm	82-50-905	6 mm	30 mm
		dia. 6 mm	82-50-906	X	6 mm
		dia. 7.1 mm	82-50-971		
		dia. 8 mm	82-50-908		
for ground clips		Welding element	Order No.	✓	✓
		b = 6.3 mm	82-50-050		
for CD ISO nails		Welding element dia.	Order No.	Length from min. to max.	Length from min. to max.
		dia. 2 mm	82-50-020	20 mm	20 mm
		dia. 3 mm	82-50-030		
		dia. 2.7 mm	82-50-027		

¹⁾ with standard stop pin



²⁾ additional stop pin 80-90-710 necessary

Centering device	Leg assembly PSI-2	usable with stud welding unit:		
for exact positioning in templates by adjusting the concentricity of the chuck to the centering device, chuck extension necessary Centering tube Ø 20 mm: 80-40-082 Ø 26 mm: 80-40-086 Ø 30 mm: 80-40-083 Centering disc Ø 20 mm: 80-40-092 Ø 26 mm: 80-40-096 Ø 30 mm: 80-40-093 Cylindrical pin 80-10-092 Foot ring TK 38 80-40-521 Chuck extension 80-40-081 Centering device: dia. 20 mm: 92-40-111 / dia. 26 mm: 92-40-117 / dia. 30 mm: 92-40-119 <u>assembled:</u> 	for longer ISO nails and welding elements Foot piece with plastic insert 80-40-127 Clamp plate 80-40-126 Tripod leg 80-40-130 Foot 80-40-306 Foot ring 80-40-373 Leg assembly PSI-2 92-40-043 (ISO leg assembly, 3-point rest) <u>assembled:</u> 	CDi 1502 with ground cable 92-40-095 CDi 2302 with ground cable 92-40-095 CDi 3102 with ground cable 92-40-095   		
Length	Length			
from min.	from min.			
to max.	to max.			
6 mm	6 mm ⁵⁾	✓	✓	✓
30 mm	175 mm ⁵⁾	✓	✓	✓
6 mm ⁴⁾	6 mm ⁵⁾	✓	✓	✓
20 mm ⁴⁾	175 mm ⁵⁾	✓	✓	✓
✗	✗	✓	✓	✓
✗	✗	✓	✓	✗
✗	20 mm ⁵⁾ / 110 mm ⁵⁾	✓	✗	✗
	110 mm ⁵⁾ / 255 mm ⁶⁾	✓	✗	✗

⁴⁾ only in conjunction with 92-40-119

⁵⁾ when used without plastic insert

⁶⁾ when used with plastic insert



Equipment				Foot ring with feet (Standard equipment)	Foot ring TK 38 with feet																																						
Chucks				universal application on flat surfaces (pitch circle dia. 34 mm)  Foot ring: 80-40-373 Foot: 80-40-049 <u>assembled:</u> 	larger pitch circle dia. (38 mm) for higher stability when placing on the workpiece  Foot ring 80-40-521 Foot: 80-40-077 <u>assembled:</u> 																																						
	for CD threaded studs / pins	 <table><tr><td>Welding element dia.</td><td>Order No.</td></tr><tr><td>dia. 2 mm</td><td>82-50-002</td></tr><tr><td>dia. 2.5 mm</td><td>82-50-025</td></tr><tr><td>dia. 3 mm</td><td>82-50-003</td></tr><tr><td>dia. 4 mm</td><td>82-50-004</td></tr><tr><td>dia. 5 mm</td><td>82-50-005</td></tr><tr><td>dia. 6 mm</td><td>82-50-006</td></tr><tr><td>dia. 7.1 mm</td><td>82-50-071</td></tr><tr><td>dia. 8 mm</td><td>82-50-008</td></tr><tr><td>dia. 10 mm</td><td>82-50-009</td></tr></table>			Welding element dia.	Order No.	dia. 2 mm	82-50-002	dia. 2.5 mm	82-50-025	dia. 3 mm	82-50-003	dia. 4 mm	82-50-004	dia. 5 mm	82-50-005	dia. 6 mm	82-50-006	dia. 7.1 mm	82-50-071	dia. 8 mm	82-50-008	dia. 10 mm	82-50-009	<table><tr><td colspan="2">Length</td></tr><tr><td>from min.</td><td>to max.</td></tr><tr><td colspan="2"> </td></tr><tr><td>6 mm¹⁾ / 16 mm²⁾</td><td>30 mm¹⁾ / 40 mm²⁾</td></tr></table>		Length		from min.	to max.			6 mm ¹⁾ / 16 mm ²⁾	30 mm ¹⁾ / 40 mm ²⁾	<table><tr><td colspan="2">Length</td></tr><tr><td>from min.</td><td>to max.</td></tr><tr><td colspan="2"> </td></tr><tr><td>6 mm¹⁾ / 16 mm²⁾</td><td>30 mm¹⁾ / 40 mm²⁾</td></tr></table>		Length		from min.	to max.			6 mm ¹⁾ / 16 mm ²⁾
Welding element dia.		Order No.																																									
dia. 2 mm	82-50-002																																										
dia. 2.5 mm	82-50-025																																										
dia. 3 mm	82-50-003																																										
dia. 4 mm	82-50-004																																										
dia. 5 mm	82-50-005																																										
dia. 6 mm	82-50-006																																										
dia. 7.1 mm	82-50-071																																										
dia. 8 mm	82-50-008																																										
dia. 10 mm	82-50-009																																										
Length																																											
from min.	to max.																																										
6 mm ¹⁾ / 16 mm ²⁾	30 mm ¹⁾ / 40 mm ²⁾																																										
Length																																											
from min.	to max.																																										
6 mm ¹⁾ / 16 mm ²⁾	30 mm ¹⁾ / 40 mm ²⁾																																										
for CD studs with internal thread	 <table><tr><td>Welding element dia.</td><td>Order No.</td></tr><tr><td>dia. 5 mm</td><td>82-50-905</td></tr><tr><td>dia. 6 mm</td><td>82-50-906</td></tr><tr><td>dia. 7.1 mm</td><td>82-50-971</td></tr><tr><td>dia. 8 mm</td><td>82-50-908</td></tr></table>			Welding element dia.	Order No.	dia. 5 mm	82-50-905	dia. 6 mm	82-50-906	dia. 7.1 mm	82-50-971	dia. 8 mm	82-50-908	<table><tr><td colspan="2">Length</td></tr><tr><td>from min.</td><td>to max.</td></tr><tr><td colspan="2"> </td></tr><tr><td>6 mm</td><td>30 mm</td></tr></table>		Length		from min.	to max.			6 mm	30 mm	<table><tr><td colspan="2">Length</td></tr><tr><td>from min.</td><td>to max.</td></tr><tr><td colspan="2"> </td></tr><tr><td>6 mm</td><td>30 mm</td></tr></table>		Length		from min.	to max.			6 mm	30 mm										
	Welding element dia.	Order No.																																									
dia. 5 mm	82-50-905																																										
dia. 6 mm	82-50-906																																										
dia. 7.1 mm	82-50-971																																										
dia. 8 mm	82-50-908																																										
Length																																											
from min.	to max.																																										
6 mm	30 mm																																										
Length																																											
from min.	to max.																																										
6 mm	30 mm																																										
for ground clips	 <table><tr><td>Welding element</td><td>Order No.</td></tr><tr><td>b = 6.3 mm</td><td>82-50-050</td></tr></table>			Welding element	Order No.	b = 6.3 mm	82-50-050																																				
	Welding element	Order No.																																									
b = 6.3 mm	82-50-050																																										
for CD ISO nails	 <table><tr><td>Welding element dia.</td><td>Order No.</td></tr><tr><td>dia. 2 mm</td><td>82-50-020</td></tr><tr><td>dia. 3 mm</td><td>82-50-030</td></tr><tr><td>dia. 2.7 mm</td><td>82-50-027</td></tr></table>			Welding element dia.	Order No.	dia. 2 mm	82-50-020	dia. 3 mm	82-50-030	dia. 2.7 mm	82-50-027	<table><tr><td colspan="2">Length</td></tr><tr><td>from min.</td><td>to max.</td></tr><tr><td colspan="2"> </td></tr><tr><td>20 mm</td><td>80 mm</td></tr></table>		Length		from min.	to max.			20 mm	80 mm	<table><tr><td colspan="2">Length</td></tr><tr><td>from min.</td><td>to max.</td></tr><tr><td colspan="2"> </td></tr><tr><td>20 mm</td><td>80 mm</td></tr></table>		Length		from min.	to max.			20 mm	80 mm												
	Welding element dia.	Order No.																																									
dia. 2 mm	82-50-020																																										
dia. 3 mm	82-50-030																																										
dia. 2.7 mm	82-50-027																																										
Length																																											
from min.	to max.																																										
20 mm	80 mm																																										
Length																																											
from min.	to max.																																										
20 mm	80 mm																																										

¹⁾ with standard stop pin

²⁾ additional stop pin 80-90-710 necessary


Distance ring with foot ring and feet	Offset chuck adaptor with foot ring and feet	usable with stud welding unit:
for longer welding elements and welding elements with dia. 10 mm  Foot ring: 80-40-373 Distance ring 92-40-010 with screws Foot: 80-40-049 <u>assembled:</u> 	for welding in corners (minimum distance 9 mm)  Offset chuck adaptor: 82-40-011 Foot ring: 80-40-373 Foot: 80-40-049 <u>assembled:</u> 	CDi 508 with ground cable 92-40-095 
Length from min. to max.	Length from min. to max.	
15 mm¹⁾ 25 mm²⁾ 45 mm¹⁾ / 55 mm²⁾³⁾	6 mm 40 mm	✓
15 mm 30 mm	✗	✗
Length from min. to max.	Length from min. to max.	
25 mm 45 mm	6 mm 35 mm	✓
✗	✗	✓
✗	✗	✓

³⁾ stop pin 80-90-710 included in delivery of distance ring 92-40-010

Equipment			Noise damping tube	Centering tube																																						
Chucks			for reducing noise level during welding, for welding elements up to dia. 5 mm  Noise damping tube: 82-40-016 assembled:  Ø 35 mm	for welding in templates and for protection against welding sparks  Centering tube: 80-40-513 assembled:  Ø 30 mm																																						
	for CD threaded studs / nails		<table><tr><td>Welding element dia.</td><td>Order No.</td></tr><tr><td>dia. 2 mm</td><td>82-50-002</td></tr><tr><td>dia. 2.5 mm</td><td>82-50-025</td></tr><tr><td>dia. 3 mm</td><td>82-50-003</td></tr><tr><td>dia. 4 mm</td><td>82-50-004</td></tr><tr><td>dia. 5 mm</td><td>82-50-005</td></tr><tr><td>dia. 6 mm</td><td>82-50-006</td></tr><tr><td>dia. 7.1 mm</td><td>82-50-071</td></tr><tr><td>dia. 8 mm</td><td>82-50-008</td></tr><tr><td>dia. 10 mm</td><td>82-50-009</td></tr></table>	Welding element dia.	Order No.	dia. 2 mm	82-50-002	dia. 2.5 mm	82-50-025	dia. 3 mm	82-50-003	dia. 4 mm	82-50-004	dia. 5 mm	82-50-005	dia. 6 mm	82-50-006	dia. 7.1 mm	82-50-071	dia. 8 mm	82-50-008	dia. 10 mm	82-50-009	<table><tr><td colspan="2">Length</td></tr><tr><td>from min.</td><td>to max.</td></tr><tr><td>6 mm¹⁾ / 16 mm²⁾</td><td>30 mm¹⁾ / 40 mm²⁾</td></tr><tr><td colspan="2">X</td></tr><tr><td colspan="2">X</td></tr></table>	Length		from min.	to max.	6 mm ¹⁾ / 16 mm ²⁾	30 mm ¹⁾ / 40 mm ²⁾	X		X		<table><tr><td colspan="2">Length</td></tr><tr><td>from min.</td><td>to max.</td></tr><tr><td>6 mm¹⁾ / 16 mm²⁾</td><td>30 mm¹⁾ / 40 mm²⁾</td></tr><tr><td colspan="2">X</td></tr></table>	Length		from min.	to max.	6 mm ¹⁾ / 16 mm ²⁾	30 mm ¹⁾ / 40 mm ²⁾	X
Welding element dia.		Order No.																																								
dia. 2 mm		82-50-002																																								
dia. 2.5 mm		82-50-025																																								
dia. 3 mm		82-50-003																																								
dia. 4 mm		82-50-004																																								
dia. 5 mm		82-50-005																																								
dia. 6 mm		82-50-006																																								
dia. 7.1 mm	82-50-071																																									
dia. 8 mm	82-50-008																																									
dia. 10 mm	82-50-009																																									
Length																																										
from min.	to max.																																									
6 mm ¹⁾ / 16 mm ²⁾	30 mm ¹⁾ / 40 mm ²⁾																																									
X																																										
X																																										
Length																																										
from min.	to max.																																									
6 mm ¹⁾ / 16 mm ²⁾	30 mm ¹⁾ / 40 mm ²⁾																																									
X																																										
for CD studs with internal thread		<table><tr><td>Welding element dia.</td><td>Order No.</td></tr><tr><td>dia. 5 mm</td><td>82-50-905</td></tr><tr><td>dia. 6 mm</td><td>82-50-906</td></tr><tr><td>dia. 7.1 mm</td><td>82-50-971</td></tr><tr><td>dia. 8 mm</td><td>82-50-908</td></tr></table>	Welding element dia.	Order No.	dia. 5 mm	82-50-905	dia. 6 mm	82-50-906	dia. 7.1 mm	82-50-971	dia. 8 mm	82-50-908	<table><tr><td colspan="2">Length</td></tr><tr><td>from min.</td><td>to max.</td></tr><tr><td>6 mm</td><td>30 mm</td></tr><tr><td colspan="2">X</td></tr></table>	Length		from min.	to max.	6 mm	30 mm	X		<table><tr><td colspan="2">Length</td></tr><tr><td>from min.</td><td>to max.</td></tr><tr><td>6 mm</td><td>35 mm</td></tr></table>	Length		from min.	to max.	6 mm	35 mm														
	Welding element dia.	Order No.																																								
	dia. 5 mm	82-50-905																																								
	dia. 6 mm	82-50-906																																								
	dia. 7.1 mm	82-50-971																																								
dia. 8 mm	82-50-908																																									
Length																																										
from min.	to max.																																									
6 mm	30 mm																																									
X																																										
Length																																										
from min.	to max.																																									
6 mm	35 mm																																									
for ground clips		<table><tr><td>Welding element</td><td>Order No.</td></tr><tr><td>b = 6.3 mm</td><td>82-50-050</td></tr></table>	Welding element	Order No.	b = 6.3 mm	82-50-050	✓	✓																																		
	Welding element	Order No.																																								
b = 6.3 mm	82-50-050																																									
for CD ISO nails		<table><tr><td>Welding element dia.</td><td>Order No.</td></tr><tr><td>dia. 2 mm</td><td>82-50-020</td></tr><tr><td>dia. 3 mm</td><td>82-50-030</td></tr><tr><td>dia. 2.7 mm</td><td>82-50-027</td></tr></table>	Welding element dia.	Order No.	dia. 2 mm	82-50-020	dia. 3 mm	82-50-030	dia. 2.7 mm	82-50-027	<table><tr><td colspan="2">Length</td></tr><tr><td>from min.</td><td>to max.</td></tr><tr><td>20 mm</td><td>80 mm</td></tr></table>	Length		from min.	to max.	20 mm	80 mm	<table><tr><td colspan="2">Length</td></tr><tr><td>from min.</td><td>to max.</td></tr><tr><td>20 mm</td><td>80 mm</td></tr></table>	Length		from min.	to max.	20 mm	80 mm																		
	Welding element dia.	Order No.																																								
	dia. 2 mm	82-50-020																																								
	dia. 3 mm	82-50-030																																								
dia. 2.7 mm	82-50-027																																									
Length																																										
from min.	to max.																																									
20 mm	80 mm																																									
Length																																										
from min.	to max.																																									
20 mm	80 mm																																									

¹⁾ with standard stop pin

²⁾ additional stop pin 80-90-710 necessary

Centering device	Leg assembly PSI-2	usable with stud welding unit:
for exact positioning in templates by adjusting the concentricity of the chuck to the centering device, chuck extension necessary Centering tube Ø 20 mm: 80-40-082 Ø 26 mm: 80-40-086 Ø 30 mm: 80-40-083 Centering disc Ø 20 mm: 80-40-092 Ø 26 mm: 80-40-096 Ø 30 mm: 80-40-093 Cylindrical pin 80-10-092 Chuck extension 80-40-081 Foot ring TK 38 80-40-521 Centering device: dia. 20 mm: 92-40-111 / dia. 26 mm: 92-40-117 / dia. 30 mm: 92-40-119 <u>assembled:</u> 	for longer ISO nails and welding elements Foot piece with plastic insert 80-40-127 Clamp plate 80-40-126 Tripod leg 80-40-130 Foot 80-40-306 Foot ring 80-40-373 Leg assembly PSI-2 92-40-043 (ISO leg assembly, 3-point rest) <u>assembled:</u> 	usable with stud welding unit: CDi 508 with ground cable 92-40-095 
Length from min. to max.	Length from min. to max.	
6 mm 30 mm	6 mm⁵⁾ 175 mm⁵⁾	✓
6 mm⁴⁾ 20 mm⁴⁾		
✗	Length from min. to max. 6 mm⁵⁾ 175 mm⁵⁾	✓
✗	✗	✓
✗	Length from min. to max. 20 mm⁵⁾ / 110 mm⁵⁾ 110 mm⁵⁾ / 255 mm⁵⁾	✓

⁴⁾ only in conjunction with 92-40-119

⁵⁾ when used without plastic insert

⁶⁾ when used with plastic insert

Welding gun accessories CD 3 mm to 6 mm

for C 06-3 / C 08-FS / C 08 / CA 08



Order No.:

92-40-050

consisting of:

82-50-003

Chuck M3

82-50-004

Chuck M4

82-50-005

Chuck M5

82-50-006

Chuck M6

80-40-085

Socket wrench AF 17

Welding gun accessories CD 3 mm to 8 mm

for C 06-3 / C 08-FS / C 08 / CA 08



Order No.:

92-40-018

consisting of:

82-50-003

Chuck M3

82-50-004

Chuck M4

82-50-005

Chuck M5

82-50-006

Chuck M6

82-50-008

Chuck M8


80-40-085

Socket wrench AF 17

Centering device for an exact positioning in welding templates

for C 06-3 / C 08-FS / C 08 / CA 08


1



92-40-111	Centering device dia. 20 mm complete	92-40-117	Centering device dia. 26 mm complete	92-40-119	Centering device Ø 30 mm complete
80-40-092	Centering disc dia. 20 mm	80-40-096	Centering disc dia. 26 mm	80-40-093	Centering disc dia. 30 mm
80-40-082	Centering tube dia. 20 mm	80-40-086	Centering tube dia. 26 mm	80-40-083	Centering tube dia. 30 mm
80-10-092	Cylindrical pin				
80-40-081	Chuck extension				
80-40-521	Foot ring pitch circle 38 mm				

Leg assembly PSI-2 for welding of ISO nails and studs


for C 06-3 / C 08-FS / C 08 / CA 08




92-40-043 Leg assembly ISO PSI-2 with 3-point rest complete

1	80-40-127	Foot piece with plastic insert
2	80-40-126	Clamp plate
3	80-40-306	Foot
4	80-40-373	Foot ring
5	80-40-130	Leg 8 x 220 mm

Leg assemblies – details for C 06-3 / C 08-FS / C 08 / CA 08

Equipment		Spacer with gun head	usable with stud welding unit:							
Chucks		for welding of cupped head pins  Spacer: 80-05-818 Gun head: 80-05-819 <u>assembled:</u> 	CDI 502 with ground cable 92-40-091 	CDI 1502 with ground cable 92-40-091 	Pegasar 500 accu Insulation with ground cable 92-40-091 					
	for cupped head pins  <table><tr><th>Welding element dia.</th><th>Order No.</th></tr><tr><td>Ø 30 mm</td><td>82-50-310B</td></tr><tr><td>Ø 38 mm</td><td>82-50-308A</td></tr></table>	Welding element dia.	Order No.	Ø 30 mm	82-50-310B	Ø 38 mm	82-50-308A			
Welding element dia.	Order No.									
Ø 30 mm	82-50-310B									
Ø 38 mm	82-50-308A									

Chuck for cupped head pins



82-50-310B Chuck CI 03 with magnetic holder for Ø 30 mm
82-50-308A Chuck CI 03 with magnetic holder for Ø 38 mm

1	80-90-206	Screw M4 x 8	3	80-10-0476	Magnet
2	80-41-141 80-41-128	Copper washer for 82-50-310B Copper washer for 82-50-308A	4	80-41-126	Cylinder

Welding gun accessories ISO for cupped head pins Ø 30 mm



Order No.:

92-40-066A

consisting of:



82-50-310B

Chuck CI 03 with magnetic holder for Ø 30 mm



80-10-069

Double open ended wrench 14 x 17

Welding gun accessories ISO for cupped head pins Ø 38 mm



Order No.:

92-40-063A

consisting of:



82-50-308A

Chuck CI 03 with magnetic holder for Ø 38 mm



80-10-069

Double open ended wrench 14 x 17

Accessories for ACCU-TWIN (Order No. 92-10-2280A)



Chuck	for: ACCU-TWIN with steplessly adjustable stud spacing
	V 82-55-003



Clamping nut	for: Fixing of chucks
	80-05-454



Spark protection	for: Reduce sparks (from 26 mm stud spacing) and noise protection
------------------	---

V 80-08-124A



Bellows	for: Distance between chucks is under 26 mm (higher sparkling) and noise protection
---------	---

80-20-016



Battery (rechargeable)	Lead battery 12 V, 5 Ah
---------------------------	-------------------------

80-50-1348



External power supply unit (charger)	for: charging battery
--	-----------------------

88-21-490

Accessories for ACCU-TWIN (Order No. 92-10-2380A)





Chuck	for: ACCU-TWIN with steplessly adjustable stud spacing
	V 82-55-003



Clamping nut	for: Fixing of chucks
	80-05-454



Spark protection	for: Reduce sparks (from 26 mm stud spacing) and noise protection
	V 80-08-124A



Bellows	for: Distance between chucks is under 26 mm (higher sparkling) and noise protection
	80-20-016



Battery (rechargeable)	Lead battery 12 V, 5 Ah
	80-50-1348

1

Preparation:



Grinder

for: Removing paint from heating elements

88-25-441

Charging:



Power supply unit

for: Charging the battery at the mains

88-25-438



Car adaptor
(charging cable for
12 V connection)

for: Charging the battery via 12 V connection

88-25-440

Everything close to hand:

1



Toolbag

for: Carrying accessories (chucks, tool)

for: ACCU-TWIN

88-25-192



Shoulder strap

for: Safe transport of the stud welding unit

80-10-704



Assortment box

for: Safe storage of chucks and other small parts

88-25-444

Accessories for ACCU-TWIN

Accessories for Pegasar 500 accu / Pegasar 500 accu Insulation



Version „metric“
M3 – M4 – M5 – M6

Version „imperial“
#4 – #6 – #10 – 1/4"

Version „ISO“

Quick battery change



Toolbag – everything at the ready





Battery
(rechargeable)
type Accu 150

for: welding in battery mode
LiNiCoAlO₂ battery 25.55 V, 5.7 AH, 145.64 Wh

88-23-484



Charging unit
type ACCU
CHARGER 150

for: charging the battery type Accu 150 outside of the
stud welding unit

88-23-661



Transport protection

for: transportation and shipping of the stud welding
unit with inserted battery
separating the contacts between the stud welding
unit and the battery

88-24-081



(Delivery without content)

Toolbag


for: accessories (chucks, tools)

for: Pegasar 500 accu, Pegasar 500 accu Insulation,
Visar 650


88-24-466

Equipment for A 12	Page
	30 - 31
Equipment for A 12-FL	Page
	32 - 33
Welding gun accessories for A 12 / A 12-FL	Page
	34
Leg assemblies – Detail views for A 12 / A 12-FL	Page
	35

Equipment for A 16	Page
	36 - 41
Equipment for A 22	Page
	46 - 49
Welding gun accessories for A 16 / A 22 (RD / MD (DD) / PD / UD/ ID)	Page
	50 - 52
Welding gun accessories for A 16 / A 22 (concrete anchor SD)	Page
	52 - 54
Leg assemblies – Detail views for A 16 / A 22	Page
	55 - 57

Equipment						Leg assembly PSC-1		
Chucks / Ceramic ferrule grips	 Adaptor for ARC chucks 80-05-689 (included in delivery of welding gun A 12, order no. 93-20-275)					for drawn arc stud welding with ceramic ferrule		
						 Leg assembly PSC-1 93-40-022 (Ceramic leg assembly) assembled: 		
for threaded studs type RD and PD		Welding element $\varnothing d_1$	Chuck	Ceramic ferrule grip		Stud length from min. to max.		
			Order No.	Insertion depth	Order No.	Flat	Standard	
		M6	83-50-006	7 mm	80-31-095	---	20 mm	150 mm
		M8	83-52-008	6 mm	80-31-120	15 mm	20 mm	25 mm
		M8	83-50-008	9 mm	80-31-120	20 mm	25 mm	150 mm
		M10	83-52-010	4 mm	80-31-150	15 mm	20 mm	25 mm
		M10	83-50-010	11 mm	80-31-150	20 mm	25 mm	150 mm
		M12	83-52-012	6 mm	80-31-170	15 mm	20 mm	30 mm
M12	83-50-012	13 mm	80-31-170	20 mm	30 mm	150 mm		
for threaded studs type MD (DD) and unthreaded studs (pins) type UD		Welding element $\varnothing d_1$	Chuck	Ceramic ferrule grip		Stud length from min. to max.		
			Order No.	Insertion depth	Order No.	Flat	Standard	
		M4 / $\varnothing$ 4 mm	83-50-004	6 mm	80-30-104	---	15 mm	150 mm
		M5 / $\varnothing$ 5 mm	83-50-005	6 mm	80-31-095	---	15 mm	150 mm
		M6 / $\varnothing$ 6 mm	83-50-006	7 mm	80-31-095	---	20 mm	150 mm
		M8 / $\varnothing$ 8 mm	83-52-008	6 mm	80-31-150	---	20 mm	25 mm
		M8 / $\varnothing$ 8 mm	83-50-008	9 mm	80-31-150	---	25 mm	150 mm
		M10 / $\varnothing$ 10 mm	83-52-010	4 mm	80-31-150	---	20 mm	25 mm
		M10 / $\varnothing$ 10 mm	83-50-010	11 mm	80-31-150	---	25 mm	150 mm
		M12 / $\varnothing$ 12 mm	83-52-012	6 mm	80-31-205	---	20 mm	25 mm
M12 / $\varnothing$ 12 mm	83-50-012	13 mm	80-31-205	---	25 mm	150 mm		
for studs with internal thread type ID		Welding element	Chuck	Ceramic ferrule grip		Stud length from min. to max.		
		$\varnothing d_2$ $\varnothing d_1$	Order No.	Insertion depth	Order No.	Flat	Standard	
		10 M5 / M6	83-52-010	4 mm	80-31-150	---	20 mm	25 mm
		10 M5 / M6	83-50-010	11 mm	80-31-150	---	25 mm	150 mm
		12 M8	83-52-012	6 mm	80-31-205	---	20 mm	25 mm
		12 M8	83-50-012	13 mm	80-31-205	---	25 mm	150 mm

usable with stud welding unit:				
Visar 650 with ground cable 93-40-020	ARC 800 with ground cable 93-40-020	IT 1002 with ground cable 93-40-020	Visar 1200 with ground cable 93-40-020	IT 2002 with 2x ground cable 93-40-019 (for welding elements to M20)
				
✓ (up to M10 type RD)	✓ (up to M12 type RD)	✓	✓	✓
✗				
✓	✗			
✓	✓	✓	✓	✓
✗				
✗	✗			
✗	✓	✓	✓	✓
✗	✗			

Equipment						Leg assembly PSC-1		
Chucks / Ceramic ferrule grips	 Adaptor for ARC chuck 80-05-689 (included in delivery of welding gun A 12, order no. 93-20-260)					for drawn arc stud welding with ceramic ferrule		
						 Leg assembly PSC-1 93-40-022 (Ceramic leg assembly) assembled:		
for threaded studs type RD and PD		Welding element $\varnothing d_1$		Chuck		Ceramic ferrule grip		
				Order No.	Insertion depth	Order No.		
		M6		83-50-006	7 mm	80-31-095		
		M8		83-52-008	6 mm	80-31-120		
		M8		83-50-008	9 mm	80-31-120		
		M10		83-52-010	4 mm	80-31-150		
		M10		83-50-010	11 mm	80-31-150		
		M12		83-52-012	6 mm	80-31-170		
M12		83-50-012	13 mm	80-31-170				
						Stud length (see below) from min. to max.		
						Flat	Standard	
								
						---	20 mm	150 mm
						15 mm	20 mm	25 mm
						20 mm	25 mm	150 mm
						15 mm	20 mm	25 mm
						20 mm	25 mm	150 mm
						15 mm	20 mm	30 mm
						20 mm	30 mm	150 mm
for threaded studs type MD (DD) and unthreaded studs (pins) type UD		Welding element $\varnothing d_1$		Chuck		Ceramic ferrule grip		
				Order No.	Insertion depth	Order No.		
		M4 / $\varnothing 4$ mm		83-50-004	6 mm	80-30-104		
		M5 / $\varnothing 5$ mm		83-50-005	6 mm	80-31-095		
		M6 / $\varnothing 6$ mm		83-50-006	7 mm	80-31-095		
		M8 / $\varnothing 8$ mm		83-52-008	6 mm	80-31-150		
		M8 / $\varnothing 8$ mm		83-50-008	9 mm	80-31-150		
		M10 / $\varnothing 10$ mm		83-52-010	4 mm	80-31-150		
		M10 / $\varnothing 10$ mm		83-50-010	11 mm	80-31-150		
		M12 / $\varnothing 12$ mm		83-52-012	6 mm	80-31-205		
		M12 / $\varnothing 12$ mm		83-50-012	13 mm	80-31-205		
								Stud length from min. to max.
						Flat	Standard	
								
						---	15 mm	150 mm
						---	15 mm	150 mm
						---	20 mm	150 mm
						---	20 mm	25 mm
						---	25 mm	150 mm
						---	20 mm	25 mm
						---	25 mm	150 mm
						---	20 mm	25 mm
						---	25 mm	150 mm
for studs with internal thread type ID		Welding element		Chuck		Ceramic ferrule grip		
		$\varnothing d_2$	$\varnothing d_1$	Order No.	Insertion depth	Order No.		
		10	M5 / M6	83-52-010	4 mm	80-31-150		
		10	M5 / M6	83-50-010	11 mm	80-31-150		
		12	M8	83-52-012	6 mm	80-31-205		
		12	M8	83-50-012	13 mm	80-31-205		
								Stud length from min. to max.
						Flat	Standard	
								
						---	20 mm	25 mm
						---	25 mm	150 mm
						---	20 mm	25 mm
						---	25 mm	150 mm

usable with stud welding unit:				
Visar 650 with ground cable 93-40-020 	ARC 800 with ground cable 93-40-020 	IT 1002 with ground cable 93-40-020 	Visar 1200 with ground cable 93-40-020 	IT 2002 with 2x ground cable 93-40-019 (for welding elements to M20) 
 (up to M10 type RD)	 (up to M12 type RD)			
				
				
				
				
				
				
				

Welding gun accessories ARC ceramic Ø 6 mm to 12 mm

for A 12 / A 12-FL



Order No.:

93-41-012

consisting of:

suitable for leg assembly:

93-40-022



83-50-006
83-50-008
83-50-010
83-50-012

Chuck ARC M6 ceramic
Chuck ARC M8 ceramic
Chuck ARC M10 ceramic
Chuck ARC M12 ceramic



80-31-095
80-31-120
80-31-150
80-31-170
80-31-205

Ceramic ferrule grip RD5/RD6/DD5/DD6
Ceramic ferrule grip RD8
Ceramic ferrule grip DD8/DD10/RD10
Ceramic ferrule grip RD12
Ceramic ferrule grip DD12/RD16



80-10-069

Double open ended wrench 14 x 17



80-10-1022
80-10-073
80-10-075
80-10-104
80-10-126
80-10-832

Allen key 2 mm
Allen key 3 mm
Allen key 5 mm
Allen key 4 mm long
Allen key 2.5 mm
Allen key 8 mm



Welding gun accessories ARC ceramic Ø 6 mm to 10 mm

for A 12 A / 12-FL



Order No.:

93-41-010

consisting of:

suitable for leg assembly:

93-40-022



83-50-006
83-50-008
83-50-010

Chuck ARC M6 ceramic
Chuck ARC M8 ceramic
Chuck ARC M10 ceramic



80-31-095
80-31-120
80-31-150

Ceramic ferrule grip RD5/RD6/DD5/DD6
Ceramic ferrule grip RD8
Ceramic ferrule grip DD8/DD10/RD10



80-10-069

Double open ended wrench 14 x 17




80-10-1022
80-10-073
80-10-075
80-10-104
80-10-126
80-10-832

Allen key 2 mm
Allen key 3 mm
Allen key 5 mm
Allen key 4 mm long
Allen key 2.5 mm
Allen key 8 mm



Tripod leg guidance complete

for A 12



Order No.:


93-40-129

Description

1	80-40-409	Leg guidance
2	80-90-144	Screw DIN 916 M5 x 5
3	80-10-834	Knurled cap screw, flat

Tripod leg guidance complete

for A 12-FL



Order No.:

93-40-130


Description

1	80-40-409	Leg guidance
2	80-90-144	Screw DIN 916 M5 x 5
3	80-90-205	Screw DIN 913 M3 x 6

Ceramic leg assembly PSC-1

for welding of drawn arc welding elements Ø 6 to 12 mm up to l = 150 mm with ceramic ferrule

for A 12 / A 12-FL





93-40-022 Ceramic leg assembly PSC-1 complete


1	80-40-410	Foot piece Aluminium, d = 22 mm		
2	80-40-411	Leg 8 x 220 mm	alternative: 80-40-533	Leg 8 x 400 mm

Equipment						Ceramic leg assembly PSC-2		
Chucks / Ceramic ferrule grips						for drawn arc stud welding with ceramic ferrule		
for threaded studs type RD and PD						Stud length from min. to max.		
						Flat Standard		
for threaded studs type MD (DD) and unthreaded studs (pins) type UD						Stud length from min. to max.		
						Flat Standard		
for studs with internal thread type ID						Stud length from min. to max.		
						Flat Standard		

Ceramic leg assembly PSC-2			usable with stud welding unit:			
for drawn arc stud welding with ceramic ferrule  Leg assembly PSC-2 93-40-040 (Ceramic leg assembly, Foot piece dia. 28 mm) <u>assembled:</u> 			ARC 800 with ground cable 93-40-020 	IT 1002 with ground cable 93-40-020 	Visar 1200 with ground cable 93-40-020 	IT 2002 with 2x ground cable 93-40-019 (for welding elements to M20) 
Stud length from min. to max. Flat Standard   			 (up to M12 type RD)	 (up to M16 type RD)		
25	30	170				
30	35	170				
Stud length from min. to max. Flat Standard   						
						
						
25	30	170				
30	35	170				
Stud length from min. to max. Flat Standard   						
						
25	30	170				
30	35	170				

Equipment					Ceramic leg assembly PSC-2		
Chucks / Ceramic ferrule grips					for drawn arc stud welding with ceramic ferrule		
					 Leg assembly PSC-2 93-40-028 (Ceramic leg assembly, Foot piece dia. 22 mm) <u>mounted:</u> 		
for shear connectors / concrete anchors type SD	 	Welding element Ø d ₁	Chuck	Ceramic ferrule grip		Stud length	
			Order No.	Insertion depth	Order No.	from min.	to max.
						Standard	Standard
		6 mm / 1/4"	83-53-006	6 mm	80-30-206		
		10 mm / 3/8"	83-53-010	9 mm	80-30-210	50	150
		13 mm / 1/2"	83-53-012	8 mm	80-31-213	50	150
		13 mm / 1/2"	83-53-012	8 mm	80-30-213	45	150
		16 mm / 5/8"	83-53-019	12 mm	80-30-219		✗
		19 mm / 3/4"	83-53-019	12 mm	80-30-219		✗
		22 mm / 7/8"	83-53-022	12 mm	80-30-222		✗
25 mm / 1"	83-53-025	13 mm	88-15-823		✗		

Ceramic leg assembly PSC-2		Ceramic leg assembly PSC-2		Ceramic leg assembly PSC-2		usable with stud welding unit:			
for drawn arc stud welding with ceramic ferrule		for drawn arc stud welding with ceramic ferrule		for drawn arc stud welding with ceramic ferrule		ARC 800 with ground cable 93-40-020 	IT 1002 with ground cable 93-40-020 	Visar 1200 with ground cable 93-40-020 	IT 2002 with 2x ground cable 93-40-019 (for welding elements to M20) 
 Leg assembly PSC-2 93-40-040 (Ceramic leg assembly, Foot piece dia. 28 mm) <u>mounted:</u> 		 Leg assembly PSC-2 93-40-041 (Ceramic leg assembly, Foot piece dia. 29 mm) <u>mounted:</u> 		 Leg assembly PSC-2 93-40-074 (Ceramic leg assembly, Foot piece dia. 29 mm) <u>mounted:</u> 					
Stud length		Stud length		Stud length					
from min.	to max.	from min.	to max.	from min.	to max.				
Standard	Standard	Standard	Standard	Standard	Standard				
						✓	✓	✓	✓
✗		✗		✗		✗			
60	150	✗		✗					
✗		65	150	65	300	✗	✗	✗	
✗		✗		✗		✗	✗	✗	✗

Equipment				Ceramic leg assembly Y-anchor
Chucks / Ceramic ferrule grips				for drawn arc stud welding with ceramic ferrule
				 Leg assembly 93-40-125 (Ceramic leg assembly for Y-anchor) d = 19.8 mm <u>assembled:</u> 
for Y-anchor		Welding element	Chuck	Ceramic ferrule grip
		Description	Order No.	Order No.
		Y-anchor Ø 6 mm	83-50-060	not necessary
		Y-anchor Ø 8 mm	83-50-062	not necessary
for flat anchor		Welding element	Chuck	Ceramic ferrule grip
		Description	Order No.	Order No.
		Flat anchor 25 x 5 mm	83-50-315	80-31-262


Ceramic leg assembly Y-anchor		Ceramic leg assembly PSC-2		
for drawn arc stud welding with ceramic ferrule		usable with stud welding unit:		
 Leg assembly 93-40-126 (Ceramic leg assembly for Y-anchor) d = 25 mm <u>assembled:</u> 		 Leg assembly 93-40-040 (Ceramic leg assembly, Foot piece dia. 28 mm) <u>assembled:</u> 		
 IT 1002 with ground cable 93-40-020		 Visar 1200 with ground cable 93-40-020		
 IT 2002 with 2x ground cable 93-40-019 (for welding elements to M20)				
				
				
				
				
				
				
				

Equipment						Ceramic leg assembly PSC-2		
Chucks / Ceramic ferrule grips						for drawn arc stud welding with ceramic ferrule		
for threaded studs type RD and PD						Stud length from min. to max.		
	Welding element $\varnothing d_1$					Flat Standard		
	Order No. Insertion depth Order No.							
	M16 83-52-016 10 mm 80-30-116					25 30 170		
for threaded studs type MD (DD) and unthreaded studs (pins) type UD						Stud length from min. to max.		
	Welding element $\varnothing d_1$					Flat Standard		
	Order No. Insertion depth Order No.							
	M16 / $\varnothing 16$ mm 83-50-016 15 mm 80-31-262					--- 35 170		
for studs with internal thread type ID						Stud length from min. to max.		
	Welding element $\varnothing d_2$ $\varnothing d_1$					Flat Standard		
	Order No. Insertion depth Order No.							
	16 M10 83-50-016 15 mm 80-31-262					--- 35 170		

usable with
stud welding unit:

IT 2002
with 2x ground cable 93-40-019
(for welding elements to M20)
or
with 2x ground cable 93-40-072
(for welding elements to M22)



Equipment				Ceramic leg assembly PSC-2	
Chucks / Ceramic ferrule grips				for drawn arc stud welding with ceramic ferrule	
				 Leg assembly PSC-2 93-40-041 (Ceramic leg assembly, Foot piece dia. 29 mm) <u>assembled:</u> 	
for shear connectors / concrete anchors type SD		Welding element $\varnothing d_1$	Chuck Order No.	Ceramic ferrule grip Order No.	Stud length from min. to max.
					Standard Standard
		6 mm / 1/4"	83-53-006	6 mm 80-30-206	
		10 mm / 3/8"	83-53-010	9 mm 80-30-210	
		13 mm / 1/2"	83-53-012	8 mm 80-31-213	
		13 mm / 1/2"	83-53-012	8 mm 80-30-213	65 150
		16 mm / 5/8"	83-53-019	12 mm 80-30-219	
		19 mm / 3/4"	83-53-019	12 mm 80-30-219	65 150
		22 mm / 7/8"	83-53-022	12 mm 80-30-222	70 150
		25 mm / 1"	83-53-025	13 mm 88-15-823	

Ceramic leg assembly PSC-2		usable with stud welding unit:	
for drawn arc stud welding with ceramic ferrule  Leg assembly PSC-2 93-40-074 (Ceramic leg assembly, Foot piece dia. 29 mm) <u>assembled:</u> 		IT 2002 with 2x ground cable 93-40-019 (for welding elements to M20) or with 2x ground cable 93-40-072 (for welding elements to M22) 	
Stud length			
from min.	to max.		
Standard	Standard		
			
			
65	300		
65	300		
70	300		
			

Welding gun accessories ARC ceramic 6 mm to 12 mm

for A 16



Order no.:

93-41-012

consisting of:

suitable for leg assembly:



83-50-006

Chuck ARC M6 ceramic



83-50-008

Chuck ARC M8 ceramic



83-50-010

Chuck ARC M10 ceramic



83-50-012

Chuck ARC M12 ceramic



80-31-095

Ceramic ferrule grip RD5/RD6/DD5/DD6



80-31-120

Ceramic ferrule grip RD8



80-31-150

Ceramic ferrule grip DD8/DD10/RD10



80-31-170

Ceramic ferrule grip RD12



80-31-205

Ceramic ferrule grip DD12/RD16



80-10-069

Double open ended wrench 14 x 17



80-10-1022

Allen key 2 mm



80-10-073

Allen key 3 mm



80-10-075

Allen key 5 mm



80-10-104

Allen key 4 mm long



80-10-126

Allen key 2.5 mm



80-10-832

Allen key 8 mm



93-40-028

Welding gun accessories ARC ceramic 6 mm to 16 mm

for A 16 / A 22



Order no.:

93-41-016

consisting of:

suitable for leg assembly:



83-50-006

Chuck ARC M6 ceramic



83-50-008

Chuck ARC M8 ceramic



83-50-010

Chuck ARC M10 ceramic



83-50-012

Chuck ARC M12 ceramic



83-50-016

Chuck ARC M16 ceramic



80-31-095

Ceramic ferrule grip RD5/RD6/DD5/DD6



80-31-120

Ceramic ferrule grip RD8



80-31-150

Ceramic ferrule grip DD8/DD10/RD10



80-31-170

Ceramic ferrule grip RD12



80-31-205

Ceramic ferrule grip DD12/RD16



80-31-262

Ceramic ferrule grip DD16/RD20/DD20



80-10-069

Double open ended wrench 14 x 17



80-10-436

Double open ended wrench 19 x 22



80-10-1022

Allen key 2 mm



80-10-073

Allen key 3 mm



80-10-075

Allen key 5 mm



80-10-104

Allen key 4 mm long



80-10-126

Allen key 2.5 mm

80-10-832

Allen key 8 mm



93-40-040

28 mm

Welding gun accessories ARC ceramic M12

for A 16

2



Order no.:

93-40-082

consisting of:

suitable for leg assembly:

93-40-028



83-50-012

Chuck ARC M12 ceramic



80-31-170

Ceramic ferrule grip RD12

80-31-205

Ceramic ferrule grip DD12/RD16



80-10-069

Double open ended wrench 14 x 17



80-10-1022

Allen key 2 mm

80-10-073

Allen key 3 mm

80-10-075

Allen key 5 mm

80-10-104

Allen key 4 mm long

80-10-126

Allen key 2.5 mm

80-10-832

Allen key 8 mm



Welding gun accessories ARC ceramic M16

for A 16 / A 22



Order no.:

93-40-081

consisting of:

suitable for leg assembly:

93-40-040



83-50-016

Chuck ARC M16 ceramic



80-31-262

Ceramic ferrule grip DD16/RD20/DD20



80-10-069

Double open ended wrench 14 x 17

80-10-436

Double open ended wrench 19 x 22



80-10-1022

Allen key 2 mm

80-10-073

Allen key 3 mm

80-10-075

Allen key 5 mm

80-10-104

Allen key 4 mm long

80-10-126

Allen key 2.5 mm


80-10-832

Allen key 8 mm



Welding gun accessories ARC ceramic M16

for A 16 / A 22

		Order no.:		
		93-40-086	consisting of:	suitable for leg assembly:
	83-50-016	Chuck ARC M16 ceramic	 22 mm	93-40-028
	80-31-205 80-31-262	Ceramic ferrule grip DD12/RD16 Ceramic ferrule grip DD16/RD20/DD20		(Foot piece 80-40-177)
	80-10-069 80-10-436	Double open ended wrench 14 x 17 Double open ended wrench 19 x 22	 28 mm	93-40-040
	80-10-1022 80-10-073 80-10-075	Allen key 2 mm Allen key 3 mm Allen key 5 mm		(Foot piece 80-40-201)
	80-10-104 80-10-126	Allen key 4 mm long Allen key 2.5 mm		
	80-10-072 80-10-832	Allen key 1.5 mm Allen key 8 mm		
	80-40-177 80-40-201	Foot piece ceramic up to M12, d = 22 mm Foot piece ceramic for M16, d = 28 mm		

Welding gun accessories ARC concrete anchors 1/2"

for A 16

		Order no.:		
		93-40-083	consisting of:	suitable for leg assembly:
	83-53-012	Chuck ARC 1/2" concrete anchors	 22 mm	93-40-028
	80-31-213	Ceramic ferrule grip 1/2" (22 mm)		
	80-10-069 80-10-436	Double open ended wrench 14 x 17 Double open ended wrench 19 x 22	 22 mm	
	80-10-1022 80-10-073 80-10-075	Allen key 2 mm Allen key 3 mm Allen key 5 mm		
	80-10-104 80-10-126	Allen key 4 mm long Allen key 2.5 mm		
	80-10-832	Allen key 8 mm		

Welding gun accessories ARC concrete anchors 1/2"

for A 16



Order no.:

93-40-008

consisting of:

suitable for leg assembly:



83-53-012

Chuck ARC 1/2" concrete anchors



80-30-213

Ceramic ferrule grip 1/2" (28 mm)



80-10-069

Double open ended wrench 14 x 17

80-10-436

Double open ended wrench 19 x 22



80-10-1022

Allen key 2 mm

80-10-073

Allen key 3 mm

80-10-075

Allen key 5 mm

80-10-104

Allen key 4 mm long

80-10-126

Allen key 2.5 mm

80-10-832

Allen key 8 mm



93-40-040

Welding gun accessories ARC concrete anchors 3/4" and 5/8"

for A 16 / A 22



Order no.:

93-40-010

consisting of:

suitable for leg assembly:



83-53-019

Chuck ARC 3/4" and 5/8" concrete anchors



80-30-219

Ceramic ferrule grip 3/4" and 5/8" (29 mm)



80-10-069

Double open ended wrench 14 x 17

80-10-436

Double open ended wrench 19 x 22



80-10-1022

Allen key 2 mm

80-10-073

Allen key 3 mm

80-10-075

Allen key 5 mm

80-10-104

Allen key 4 mm long

80-10-126

Allen key 2.5 mm

80-10-832

Allen key 8 mm



93-40-041



93-40-074



Order no.:

93-40-011

consisting of:

suitable for leg assembly:



83-53-022

Chuck ARC 7/8" concrete anchors



80-30-222

Ceramic ferrule grip 7/8" (29 mm)



80-10-069

Double open ended wrench 14 x 17

80-10-436

Double open ended wrench 19 x 22



80-10-1022

Allen key 2 mm

80-10-073

Allen key 3 mm

80-10-075

Allen key 5 mm

80-10-104

Allen key 4 mm long

80-10-126

Allen key 2.5 mm

80-10-832

Allen key 8 mm

29 mm

93-40-041


29 mm

93-40-074

Ceramic leg assembly PSC-2

for welding of ARC welding elements dia. 4 to 12 mm up to l=170 mm with ceramic ferrule

for A 16



93-40-028 Ceramic leg assembly PSC-2 complete

①

80-40-177

Foot piece, d = 22 mm

②

80-40-110

Leg 10 x 240 mm


alternative: 80-40-493

Leg 10 x 390 mm

Ceramic leg assembly PSC-2

for welding of ARC welding elements dia. 16 to 20 mm up to l=170 mm with ceramic ferrule

for A 16 / A 22




93-40-040 Ceramic leg assembly PSC-2 complete

- ① 80-40-201 Foot piece, d = 28 mm
- ② 80-40-110 Leg 10 x 240 mm alternative: 80-40-493 Leg 10 x 390 mm

Ceramic leg assembly PSC-2

for welding of ARC concrete anchors 5/8" - 7/8" up to l=150 mm with ceramic ferrule

for A 16 / A 22




93-40-041 Ceramic leg assembly PSC-2 complete

- ① 80-41-028 Foot piece, d = 29 mm
- ② 80-40-110 Leg 10 x 240 mm alternative: 80-40-493 Leg 10 x 390 mm

Ceramic leg assembly PSC-2




for welding of ARC concrete anchors 5/8" - 7/8" up to l=300 mm with ceramic ferrule

for A 16 / A 22





93-40-074 Ceramic leg assembly PSC-2 complete

- ① 80-41-028 Foot piece, d = 29 mm
- ② 80-40-493 Leg 10 x 390 mm


Equipment for A 12	Page
	54 - 55
Equipment for A 12-FL	Page
	62 - 63
Equipment for A 16	Page
	64 - 65

Welding gun accessories for A 12 / A 12-FL / A 16	Page
	64


Leg assemblies – Detail views for A 12 / A 12-FL / A 16	Page
	65

Equipment				Shielding gas leg assembly PSS-2	
Chucks					
	Adaptor for ARC chucks 80-05-689 (included in delivery of welding gun A 12, order no. 93-20-274)			Shielding gas leg assembly PSS-2 93-40-021 assembled:	
for threaded studs type RD and PD		Welding element Ø d ₁	Chuck Order No.	Insertion depth	Stud length from min. to max.
		M6	83-51-006	7 mm	15 150
		M8	83-51-008	9 mm	15 150
		M10	83-51-410	4 mm	10 20
		M10	83-51-010	11 mm	20 150
		M12	83-51-012	13 mm	20 150
for threaded studs type MD (DD) and unthreaded studs (pins) type UD		Welding element Ø d ₁	Chuck Order No.	Insertion depth	Stud length from min. to max.
		M4 / Ø 4 mm	83-51-004	5 mm	10 150
		M5 / Ø 5 mm	83-51-005	4 mm	10 150
		M6 / Ø 6 mm	83-51-006	7 mm	15 150
		M8 / Ø 8 mm	83-51-008	9 mm	15 150
		M10 / Ø 10 mm	83-51-410	4 mm	10 20
		M10 / Ø 10 mm	83-51-010	11 mm	20 150
		M12 / 1 Ø 0 mm	83-51-012	13 mm	20 150
for studs with internal thread type ID		Welding element Ø d ₂ Ø d ₁	Chuck Order No.	Insertion depth	Stud length from min. to max.
		10 mm M5 / M6	83-51-410	4 mm	10 20
		10 mm M6 / M6	83-51-010	11 mm	20 150
		12 mm M8	83-51-012	13 mm	20 150
for SC collar studs with flange nut		Welding element Ø d ₁	Chuck Order No.	Insertion depth	h ₁ from min. to max.
		14.5 mm	83-51-146	4 mm	--- 20

usable with stud welding unit:					
Visar 650 (shielding gas version) with ground cable 93-40-020	ARC 800 with ground cable 93-40-020	IT 1002 with ground cable 93-40-020	Visar 1200 with ground cable 93-40-020	IT 2002 with 2x ground cable 93-40-019 (for welding elements to M20)	IT 90 with 2x ground cable 93-40-019 (for welding elements to M20)
					
✓ (up to M10 Typ RD)	✓ (up to M12 type RD)	✓	✓	✓	✓
✗					
✓	✗				
✓	✓	✓	✓	✓	✓
✗					
✗	✗				
✗	✓	✓	✓	✓	✓
✗	✗				
✗	✗	✓	✓	✓	✓

Equipment				Shielding gas leg assembly PSS-2																									
Chucks	 Adaptor for ARC chuck 80-05-689 (included in delivery of welding gun A 12, order no. 93-20-260)			 Shielding gas leg assembly PSS-2 93-40-021 assembled: 																									
	for threaded studs type RD and PD	 <table><tr><td>Welding element Ø d₁</td><td>Chuck Order No.</td><td>Insertion depth</td></tr><tr><td>M6</td><td>83-51-006</td><td>7 mm</td></tr><tr><td>M8</td><td>83-51-008</td><td>9 mm</td></tr><tr><td>M10</td><td>83-51-410</td><td>4 mm</td></tr><tr><td>M10</td><td>83-51-010</td><td>11 mm</td></tr><tr><td>M12</td><td>83-51-012</td><td>13 mm</td></tr></table>			Welding element Ø d ₁	Chuck Order No.	Insertion depth	M6	83-51-006	7 mm	M8	83-51-008	9 mm	M10	83-51-410	4 mm	M10	83-51-010	11 mm	M12	83-51-012	13 mm	Stud length from min. to max.						
Welding element Ø d ₁		Chuck Order No.	Insertion depth																										
M6		83-51-006	7 mm																										
M8		83-51-008	9 mm																										
M10		83-51-410	4 mm																										
M10		83-51-010	11 mm																										
M12	83-51-012	13 mm																											
			15 mm	150 mm																									
			15 mm	150 mm																									
			10 mm	20 mm																									
			20 mm	150 mm																									
			20 mm	150 mm																									
for threaded studs type MD (DD) and unthreaded studs (pins) type UD	 <table><tr><td>Welding element Ø d₁</td><td>Chuck Order No.</td><td>Insertion depth</td></tr><tr><td>M4 / Ø 4 mm</td><td>83-51-004</td><td>5 mm</td></tr><tr><td>M5 / Ø 5 mm</td><td>83-51-005</td><td>4 mm</td></tr><tr><td>M6 / Ø 6 mm</td><td>83-51-006</td><td>7 mm</td></tr><tr><td>M8 / Ø 8 mm</td><td>83-51-008</td><td>9 mm</td></tr><tr><td>M10 / Ø 10 mm</td><td>83-51-410</td><td>4 mm</td></tr><tr><td>M10 / Ø 10 mm</td><td>83-51-010</td><td>11 mm</td></tr><tr><td>M12 / Ø 12 mm</td><td>83-51-012</td><td>13 mm</td></tr></table>			Welding element Ø d ₁	Chuck Order No.	Insertion depth	M4 / Ø 4 mm	83-51-004	5 mm	M5 / Ø 5 mm	83-51-005	4 mm	M6 / Ø 6 mm	83-51-006	7 mm	M8 / Ø 8 mm	83-51-008	9 mm	M10 / Ø 10 mm	83-51-410	4 mm	M10 / Ø 10 mm	83-51-010	11 mm	M12 / Ø 12 mm	83-51-012	13 mm	Stud length from min. to max.	
	Welding element Ø d ₁	Chuck Order No.	Insertion depth																										
	M4 / Ø 4 mm	83-51-004	5 mm																										
	M5 / Ø 5 mm	83-51-005	4 mm																										
	M6 / Ø 6 mm	83-51-006	7 mm																										
	M8 / Ø 8 mm	83-51-008	9 mm																										
	M10 / Ø 10 mm	83-51-410	4 mm																										
	M10 / Ø 10 mm	83-51-010	11 mm																										
M12 / Ø 12 mm	83-51-012	13 mm																											
			10 mm	150 mm																									
			10 mm	150 mm																									
			15 mm	150 mm																									
			15 mm	150 mm																									
			10 mm	20 mm																									
			20 mm	150 mm																									
			20 mm	150 mm																									
for studs with internal thread type ID	 <table><tr><td>Welding element Ø d₂ Ø d₁</td><td>Chuck Order No.</td><td>Insertion depth</td></tr><tr><td>10 mm M5 / M6</td><td>83-51-410</td><td>4 mm</td></tr><tr><td>10 mm M6 / M6</td><td>83-51-010</td><td>11 mm</td></tr><tr><td>12 mm M8</td><td>83-51-012</td><td>13 mm</td></tr></table>			Welding element Ø d ₂ Ø d ₁	Chuck Order No.	Insertion depth	10 mm M5 / M6	83-51-410	4 mm	10 mm M6 / M6	83-51-010	11 mm	12 mm M8	83-51-012	13 mm	Stud length from min. to max.													
	Welding element Ø d ₂ Ø d ₁	Chuck Order No.	Insertion depth																										
	10 mm M5 / M6	83-51-410	4 mm																										
	10 mm M6 / M6	83-51-010	11 mm																										
	12 mm M8	83-51-012	13 mm																										
			10 mm	20 mm																									
			20 mm	150 mm																									
			20 mm	150 mm																									

usable with stud welding unit:					
Visar 650 (shielding gas version) with ground cable 93-40-020	ARC 800 with ground cable 93-40-020	IT 1002 with ground cable 93-40-020	Visar 1200 with ground cable 93-40-020	IT 2002 with 2x ground cable 93-40-019 (for welding elements to M20)	IT 90 with 2x ground cable 93-40-019 (for welding elements to M20)
					
✓ (up to M10 Typ RD)	✓ (up to M12 type RD)	✓	✓	✓	✓
✗					
✓	✗				
✓	✓	✓	✓	✓	✓
✗					
✗	✗				
✓	✓	✓	✓	✓	✓
✗	✗				

Equipment					Shielding gas leg assembly PSS-2	
Chucks						
					Shielding gas leg assembly PSS-3 93-40-017 assembled: 	
for threaded studs type RD and PD		Welding element Ø d ₁	Chuck Order No.	Insertion depth	Stud length	
					from min.	to max.
		M4	83-51-004	5 mm	10	120
		M5	83-51-005	4 mm	10	120
		M6	83-51-006	7 mm	15	120
		M8	83-51-008	9 mm	15	120
		M10	83-51-410	4 mm	10	20
		M10	83-51-010	11 mm	20	120
for threaded studs type MD (DD) and unthreaded studs (pins) type UD		Welding element Ø d ₁	Chuck Order No.	Insertion depth	Stud length	
					from min.	to max.
		M4	83-51-004	5 mm	10	120
		M5	83-51-005	4 mm	10	120
		M6	83-51-006	7 mm	15	120
		M8	83-51-008	9 mm	15	120
		M10	83-51-410	4 mm	10	20
		M10	83-51-010	11 mm	20	120
for studs with internal thread type ID		Welding element Ø d ₂	Chuck Order No.	Insertion depth	Stud length	
					from min.	to max.
		10 M5 / M6	83-51-410	4 mm	10	20
		10 M6 / M6	83-51-010	11 mm	20	120
		12 M8	83-51-012	13 mm	20	120
	16 M10	83-51-016	16 mm	30	130	

usable with stud welding unit:				
ARC 800 with ground cable 93-40-020	IT 1002 with ground cable 93-40-020	Visar 1200 with ground cable 93-40-020	IT 2002 with 2x ground cable 93-40-019 (for welding elements to M20)	IT 90 with 2x ground cable 93-40-019 (for welding elements to M20)
				
✗	✓ (up to M16 type RD)	✓	✓	✓
✓ (up to M12 type RD)				
✗				
✗	✓	✓	✓	✓
✓				
✗				
✗	✗	✓	✓	✓
✓	✓			
✗	✗			
✗	✗	✓	✓	✓
✓	✓			
✗	✗			

Welding gun accessories ARC shielding gas 6 mm to 12 mm

for A 12 / A 12-FL / A 16



Order No.:

93-40-114

consisting of:

83-51-006
83-51-008
83-51-010
83-51-012

Chuck ARC M6 Shielding gas
Chuck ARC M8 Shielding gas
Chuck ARC M10 Shielding gas
Chuck ARC M12 Shielding gas

80-10-069

Double open ended wrench 14 x 17

80-10-1022
80-10-073
80-10-075
80-10-104
80-10-126
80-10-832

Allen key 2 mm
Allen key 3 mm
Allen key 5 mm
Allen key 4 mm long
Allen key 2.5 mm
Allen key 8 mm

suitable for leg assembly:

93-40-021



93-40-017



Welding gun accessories ARC shielding gas M12

for A 12 / A 12-FL / A 16



Order No.:

93-40-084

consisting of:

83-51-012

Chuck ARC M12 Shielding gas

80-10-069

Double open ended wrench 14 x 17

80-10-1022
80-10-073
80-10-075
80-10-104
80-10-126
80-10-832

Allen key 2 mm
Allen key 3 mm
Allen key 5 mm
Allen key 4 mm long
Allen key 2.5 mm
Allen key 8 mm

suitable for leg assembly:

93-40-021



93-40-017



Protective hose, complete with zipper

for A 12 /
A 12-FL (5 m cable length)



Order No.:

80-11-430


length: 430 cm

Protects welding gun cable
and shielding gas hose against
damage and welding sparks

Shielding gas leg assembly PSS-2

for welding of ARC welding elements dia. 6 to 12 mm up to l = 150 mm with shielding gas

for A 12 / A 12-FL




93-40-021 Shielding gas leg assembly PSS-2 complete

- | | | | | |
|---|-----------|--|------------------------|----------------|
| ① | 80-40-149 | Shielding gas tube, D = 35 mm, L = 60 mm | | |
| ② | 80-40-538 | Foot piece D = 35 mm | | |
| ③ | 80-40-411 | Leg 8 x 220 mm | alternative: 80-40-533 | Leg 8 x 400 mm |
| ④ | 80-11-420 | Plastic hose | | |

Shielding gas leg assembly PSS-3


for welding of ARC welding elements dia. 6 to 12 mm up to l = 170 mm with shielding gas


for A 16



93-40-017 Shielding gas leg assembly PSS-3 complete

- | | | | | |
|---|-----------|--|------------------------|-----------------|
| ① | 80-40-149 | Shielding gas tube, D = 35 mm, L = 60 mm | | |
| ② | 80-10-112 | Foot piece D = 35 mm | | |
| ③ | 80-40-110 | Leg 10 x 240 mm | alternative: 80-40-493 | Leg 10 x 390 mm |
| ④ | 80-11-420 | Plastic hose | | |

Equipment for A 12-FL ISO	Page
	70 - 71


Equipment for A 12	Page
	72 - 73

Leg assemblies – Detail views for A 12 / A 12-FL ISO

Page



74 - 75

Equipment					Leg assembly with support tube	Leg assembly PSI-3
Chucks	 Order No. 93-20-26010				ISO leg assembly with Aluminium support tube, leg dia. 8 mm  Leg assembly with support tube (leg length = 220 mm) 93-40-044 assembled: 	ISO leg assembly with support tube and Teflon insert, leg dia. 8 mm  Leg assembly PSI-3 (leg length = 220 mm) 93-40-066 assembled: 
for short insulation pins type ND up to dia. 5 mm		Welding element dia.	Chuck Order No.	Ceramic ferrule grip	Length	
		Dia. 2 mm	80-04-958	not necessary	from min. to max.	
		Dia. 3 mm	80-04-959	not necessary	40 mm 220 mm	
		Dia. 4 mm	80-04-960	not necessary	75 mm 250 mm	
for short insulation pins type ND up to dia. 6 mm		Welding element dia.	Chuck Order No.	Ceramic ferrule grip	Length	
		Dia. 6 mm	80-04-962	80-31-095	from min. to max.	
					X	
					X	
for long insulation pins type ND up to dia. 5 mm		Welding element dia.	Chuck Order No.	Ceramic ferrule grip	Length	
		Dia. 2 mm	80-05-512	not necessary	from min. to max.	
		Dia. 3 mm	80-05-452	not necessary	90 mm 250 mm	
		Dia. 4 mm	80-05-513	not necessary	135 mm 280 mm	
for insulation pins type ND dia. 6 mm		Welding element dia.	Chuck Order No.	Ceramic ferrule grip	Length	
		Dia. 5 mm	80-04-956	not necessary	40 mm 250 mm	
					135 mm 280 mm	
					X	
for Fiberfix pins		Welding element dia.	Chuck Order No.	Ceramic ferrule grip	Length	
		Dia. 6 mm	80-04-957	80-31-095	from min. to max.	
					X	
					X	

Leg assembly PSI-3	Leg assembly PSC-1	Leg assembly PSC and adaptor for ARC chucks	usable with stud welding unit:			
ISO leg assembly with support tube and Teflon insert, leg dia. 8 mm  Leg assembly PSI-3 (leg length = 400 mm) 93-40-065 assembled: 	for drawn arc stud welding with ceramic ferrule  Leg assembly PSC-1 93-40-022 assembled: 	for drawn arc stud welding with ceramic ferrule  Leg assembly PSC-1 93-40-022 adaptor for ARC chucks 80-05-689 assembled: 	usable with stud welding unit: Visar 650 with ground cable 93-40-020  ARC 800 with ground cable 93-40-020  IT 1002 with ground cable 93-40-020  Visar 1200 with ground cable 93-40-020 			
Length from min. to max. 75 mm 430 mm	✗	✗	✓	✗	✓	✓
75 mm 430 mm	✗	✗	✓	✓		
✗	Length from min. to max. 40 mm 220 mm	✗	✓	✓	✓	✓
Length from min. to max. 135 mm 430 mm	✗	✗	✓	✗	✓	✓
135 mm 460 mm	✗	✗	✓	✓		
✗	Length from min. to max. 40 mm 220 mm	✗	✓	✓	✓	✓
✗	✗	Length from min. to max. 40 mm 160 mm	✓	✓	✓	✓


Equipment					Leg assembly with support tube		
Chucks	 Order No. 93-20-270				ISO leg assembly with Aluminium support tube, leg dia. 8 mm  Leg assembly with support tube (leg length = 220 mm) 93-40-044 <u>assembled:</u> 		
	for insulation pins type ND up to dia. 5 mm		Welding element dia.	Chuck Order No.	Ceramic ferrule grip	Length from min. up to max.	
			Dia. 3 mm	83-54-103	not necessary	90 mm	155 mm
			Dia. 4 mm	83-54-104	not necessary		
	Dia. 5 mm	83-54-105	not necessary				
for insulation pins type ND up to dia. 5 mm		Welding element dia.	Chuck Order No.	Ceramic ferrule grip	Length from min. up to max.		
		Dia. 3 mm	83-50-1346	not necessary	45 mm	155 mm	
		Dia. 4 mm	83-50-1446	not necessary			
Dia. 5 mm	83-50-1546	not necessary					
for insulation pins type ND dia. 3 and 4 mm		Welding element dia.	Chuck Order No.	Ceramic ferrule grip	Length from min. up to max.		
		Dia. 3 mm	83-55-103	not necessary	30 mm	160 mm	
		Dia. 4 mm	83-55-104	not necessary			
for Fiberfix pins		Welding element dia.	Chuck Order No.	Ceramic ferrule grip	Length from min. up to max.		
Dia. 5 mm	83-50-011	80-30-105	40 mm	160 mm			

Leg assembly with support tube		usable with stud welding unit:			
ISO leg assembly with Aluminium support tube, leg dia. 8 mm  Leg assembly with support tube (leg length = 390 mm) 93-40-026 <u>assembled:</u> 		Visar 650 with ground cable 93-40-020 	ARC 800 with ground cable 93-40-020 	IT 1002 with ground cable 93-40-020 	Visar 1200 with ground cable 93-40-020 
Length from min.	up to max.	✓	✗	✓	✓
90 mm	355 mm		✓		
Length from min.	up to max.	✓	✗	✓	✓
45 mm	355 mm		✓		
Length from min.	up to max.	✓	✗	✓	✓
30 mm	360 mm				
Length from min.	up to max.	✓	✓	✓	✓
40 mm	360 mm				

ISO leg assembly PSI

for welding of ISO pins type ND dia. 3 to 5 mm

for A 12 / A 12- FL



93-40-044 ISO Leg assembly PSI complete

- | | | | |
|---|-----------|---------------------------|---------------------------------------|
| ① | 80-05-451 | Supporting tube D = 22 mm | |
| ② | 80-40-410 | Foot piece d = 22 mm | |
| ③ | 80-40-411 | Leg 8 x 220 mm | alternative: 80-40-533 Leg 8 x 400 mm |

ISO leg assembly PSI

for welding of ISO pins type ND dia. 3 to 6 mm

for A 12 / A 12- FL




93-40-026 ISO Leg assembly PSI complete

- | | | |
|---|-----------|----------------------|
| ① | 80-40-623 | Supporting tube HGW |
| ② | 80-40-410 | Foot piece d = 22 mm |
| ③ | 80-40-533 | Leg 8 x 400 mm |

ISO leg assembly PSI-3

for welding of ISO pins type ND dia. 3 to 5 mm

for A 12 / A 12-FL



ISO Leg assembly PSI-3 complete

93-40-066

- | | | |
|---|-----------|--|
| ① | 80-40-411 | Leg 8 x 220 mm |
| ② | 80-11-001 | Supporting tube Alu with Teflon insert |
| ③ | 80-40-538 | Foot piece d = 35 mm |


93-40-065

- | | |
|-----------|--|
| 80-40-533 | Leg 8 x 400 mm |
| 80-11-001 | Supporting tube Alu with Teflon insert |
| 80-40-538 | Foot piece d = 35 mm |

Ceramic leg assembly PSC-1

for welding of ISO pins typ ND dia. 6 mm and ARC-Fiberfix-pins dia. 5 mm up to l=160 mm
with ceramic ferrule

for A 12 / A 12-FL




93-40-022 Ceramic leg assembly PSC-1 complete

- | | | | | |
|---|-----------|---------------------------------|------------------------|----------------|
| ① | 80-40-410 | Foot piece Aluminium, d = 22 mm | | |
| ② | 80-40-411 | Leg 8 x 220 mm | alternative: 80-40-533 | Leg 8 x 400 mm |

ISO leg assembly with support fork

for welding of ISO pins type ND dia. 3 to 6 mm on finned walls

for A 12 / A 12-FL



ISO leg assembly with fork support complete

93-40-052

- | | | | | |
|---|-----------|-------------------------------|-----------------------|----------------|
| ① | 80-41-154 | Support fork for finned walls | | |
| ② | 80-11-090 | Teflon insert | | |
| ③ | 80-40-538 | Foot piece d = 35 mm | | |
| ④ | 80-40-411 | Leg 8 x 220 mm | alternative 80-40-533 | Leg 8 x 400 mm |

Equipment for A 12	Page
	78 - 79

Welding gun accessories for CA 08 / A 12	Page
	80

Leg assemblies – Detail views for CA 08 / A 12	Page
	83

Equipment			Centering tube PPR-2 and distance ring	Gas shroud PSS-1 and distance ring	Gas shroud PSS-1
Chucks			for Short cycle without shield. gas	for Short cycle with shielding gas	for Short cycle with shielding gas
			 Centering tube 80-40-513 distance ring 88-21-548 assembled: Ø 30 mm	 Gas shroud (l=79 mm) 92-40-051 distance ring 88-21-548 assembled: Ø 30 mm	 Gas shroud (l=85 mm) 92-41-051 assembled: Ø 30 mm
for SC threaded studs and pins		Welding element dia. Order No.	Stud length from min. to max.		Stud length from min. to max.
		Ø 2 mm 82-50-002	8 mm ¹⁾³⁾	30 mm ¹⁾³⁾	15 mm ¹⁾³⁾
		Ø 2.5 mm 82-50-025	/	/	/
		Ø 3 mm 82-50-003	16 mm ²⁾³⁾	40 mm ²⁾³⁾	25 mm ²⁾³⁾
		Ø 4 mm 82-50-004	8 mm ¹⁾³⁾	30 mm ¹⁾³⁾	15 mm ¹⁾³⁾
		Ø 5 mm 82-50-005	/	/	/
		Ø 6 mm 82-50-006	16 mm ²⁾³⁾	40 mm ²⁾³⁾	25 mm ²⁾³⁾
		Ø 7.1 mm 82-50-071	8 mm ¹⁾³⁾	30 mm ¹⁾³⁾	15 mm ¹⁾³⁾
for studs with internal thread type ID		Welding element dia. Order No.	Stud length from min. to max.		Stud length from min. to max.
		Ø 5 mm 82-50-905	8 mm ³⁾	35 mm ³⁾	15 mm 40 mm
		Ø 6 mm 82-50-906	8 mm ³⁾	35 mm ³⁾	15 mm 40 mm
		Ø 7.1 mm 82-50-971	8 mm ³⁾	35 mm ³⁾	15 mm 40 mm
for SC collar studs with plastic cap		Welding element dia. Order No.	Stud length from min. to max.		Stud length from min. to max.
		Ø 14 mm 82-53-135	X		X
for SC collar studs with flange nut		Welding element dia. Order No.	Stud length from min. to max.		Stud length from min. to max.
		Ø 12.5 mm 82-50-125	X		X
for T studs		Welding element dia. Order No.	Stud length from min. to max.		Stud length from min. to max.
		Ø 5 mm / Ø 3 mm 82-50-060 Inlaid tool 80-41-040	3.5 mm ³⁾	7 mm ³⁾	10 mm 13 mm

¹⁾ with standard stop pin

²⁾ additional stop pin 80-90-710 necessary

³⁾ with distance ring

⁴⁾ without distance ring

Gas shroud PSS-1		usable with stud welding unit:					
for Short cycle with shielding gas							
 Gas shroud (l=88 mm) 92-44-051							
assembled:  Ø 30 mm							
for Short cycle with shielding gas							
 Gas shroud (l=95 mm) 92-42-051							
assembled:  Ø 30 mm							
		Visar 650 (without shield. gas connection) with ground cable 93-40-020 	Visar 650 (shielding gas version) with ground cable 93-40-020 	ARC 800 with ground cable 93-40-020 	IT 1002 with ground cable 93-40-020 	Visar 1200 with ground cable 93-40-020 	IT 90 with 2x ground cable 93-40-019 (for welding elements to M20) 
Stud length from min. to max.	Stud length from min. to max.						
15 mm ¹⁾ / 25 mm ²⁾	35 mm ¹⁾ / 45 mm ²⁾	✓ (only PPR-2)	✓	✗	✓	✓	✓
15 mm ¹⁾ / 25 mm ²⁾	35 mm ¹⁾ / 45 mm ²⁾	✓ (only PPR-2)	✓	✓	✓	✓	✓
15 mm ¹⁾ / 25 mm ²⁾	35 mm ¹⁾ / 45 mm ²⁾	✗	✗	✓	✓	✓	✓
✗	15 mm	✗	✗	✗	✓	✓	✓
Stud length from min. to max.	Stud length from min. to max.						
15 mm	40 mm	✓ (only PPR-2)	✓	✓	✓	✓	✓
15 mm	40 mm	✗	✗				
✗	✓	✗	✗	✗	✓	✓	✓
✓	✗	✗	✗	✗	✓	✓	✓
Stud length from min. to max.	✗						
13 mm		✓ (only PPR-2)	✓	✗	✓	✓	✓

¹⁾ with standard stop pin

²⁾ additional stop pin 80-90-710 necessary

³⁾ with distance ring

⁴⁾ without distance ring

Welding gun accessories 3 mm to 6 mm

for A 12

	OrderNo.: 92-40-050 82-50-003 82-50-004 82-50-005 82-50-006 80-40-085	consisting of: Chuck M3 Chuck M4 Chuck M5 Chuck M6 Socket wrench AF17	suitable for leg assembly: Positioning tube / PSS-1 
---	--	--	---

Welding gun accessories 3 mm to 8 mm

for A 12

	Order No.: 92-40-018 82-50-003 82-50-004 82-50-005 82-50-006 82-50-008 80-40-085	consisting of: Chuck M3 Chuck M4 Chuck M5 Chuck M6 Chuck M8 Socket wrench AF17	suitable for leg assembly: Positioning tube / PSS-1 
---	---	---	---

Gas shroud PSS-1 for Short Cycle applications

for A 12

5



Gas shroud PSS-1

92-40-051
L = 79 mm

92-41-051
L = 85 mm

92-44-051
L = 88 mm

92-42-051
L = 95 mm

Distance ring

88-21-548

not necessary

not necessary

not necessary

for welding elements to

L = 40 mm

L = 45 mm

L = 45 mm

L = 50 mm

1

Shielding gas tube
Ø 30 mm

80-40-737
L = 42 mm

80-41-737
L = 48 mm

80-44-737
L = 51 mm

80-42-737
L = 58 mm

2

Shielding gas connection piece

80-40-736

3

Plastic hose 5.5 m

80-10-182

4

Connector male

80-10-246

5

Swivel connection

80-10-0984

Protective hose, complete with zipper

for A 12




Order No.:

80-11-430

length: 430 cm


Protects welding gun cable
and shielding gas hose against
damage and welding sparks

Leg assemblies – details for A 12



Equipment for AM 12 A	Page
	86 - 87

Equipment for AM 12 A



Equipment complete	consisting of sleeve fixture, distance washer and magnetic field guidance		
M6	V	93-40-0030068	
M8	V	93-40-003008	
M10	V	93-40-003010	
M12	V	93-40-003012	




Sleeve fixture complete	for:	AM 12 A	
	for:	Welding of welding nuts type HBS Hex ^{Nut} M6 to M12	
M6	V	88-22-532	
M8	V	88-21-107	
M10	V	88-21-108	
M12	V	88-21-109	



Field former bell	for:	AM 12 A	
		88-16-929	



Distance washer	for: AM 12 A
Ø / B	
M6 / 7 mm	V 88-18-966
M8 / 7 mm	V 88-18-966
M10 / 8 mm	V 88-21-116
M12 / 9 mm	V 88-18-967



Magnetic field guidance	for: AM 12 A
Ø / D	
M6 / 21 mm	V 88-17-266A
M8 / 21 mm	V 88-17-266A
M10 / 26 mm	V 88-17-267A
M12 / 28 mm	V 88-17-268A




Shielding gas leg assembly complete	for: AM 12 A for: Welding of welding nuts type HBS Hex ^{Nut} M6 to M12 Leg 10 x 240 mm with plastic hose, l = 5.0 m
	88-23-039

Equipment for PAH-1	Page
	86 - 97
Equipment for KAH 412	Page
	98 - 115
Equipment for VBZ-3	Page
	116 - 117
Pneumatic ground clamps	Page
	114 - 115

T-slot blocks / Zero-point stop pins	Page
	120 - 121
PBZ (pneumatic single stud feeding)	Page
	118 - 119
Further components	Page
	124 - 127
Accessories for MPW	Page
	128 - 129

The equipment, which is delivered together with the welding head, consists of standard components of your choice:



Pos.	Quantity	Description	Order No.
6	1	Feed tube	*)
7	1	Bellows	80-20-010
8	1	Piston rod	80-40-012
9	1	Plunger	*)
10	1	Pin stop	*)
11	1	Pin 2 mm	80-10-208
12	1	Guide bushing	*)
13	1	Chuck	*)
14	1	Retaining nut	80-40-010
15	1	Special wrench	84-40-010
	1	Socket wrench AF 15	80-40-085

*) Selection according to type and dimension of the welding element

Assortment box

Accessories for easy change of equipment for other length and diameter of welding element

for PAH-1

7

84-40-013A

Assortment box, manual

for feeding of standard studs Ø 3 to 8 mm by hand


84-43-013A

Assortment box, automatic

for feeding of standard studs Ø 3 to 8 mm by VBZ





Equipment for PAH-1

Equipment					9 Plunger	
Chucks					The stud is pressed through the chuck by the plunger.	
					84-40-531 (conical short) 84-40-561 (cylindrical short)	
for CD studs with dia. 3 mm		Welding element dia.	Order No. Chuck	Stud length	Order No. Plunger	
		Ø 3 mm	84-50-003	8 mm	84-40-531	
				10 mm	84-40-531	
				12 mm	84-40-531	
				15 mm	84-40-531	
				20 mm	84-40-561	
				25 mm	84-40-561	
				30 mm	84-40-561	
for CD studs with dia. 4 mm		Welding element dia.	Order No. Chuck	Stud length	Order No. Plunger	
		Ø 4 mm	84-50-004	8 mm	84-40-531	
				10 mm	84-40-531	
				12 mm	84-40-531	
				15 mm	84-40-531	
				20 mm	84-40-561	
				25 mm	84-40-561	
				30 mm	84-40-561	
for CD studs with dia. 5 mm		Welding element dia.	Order No. Chuck	Stud length	Order No. Plunger for	
		Ø 5 mm	84-50-005	8 mm	Threaded studs / pins	Internal threaded studs
				10 mm	84-40-531	84-40-561
				12 mm	84-40-531	84-40-561
				15 mm	84-40-561	84-40-561
				20 mm	84-40-561	84-40-561
				25 mm	84-40-561	84-40-561
				30 mm	84-40-561	84-40-561


12 Guide bushing	10 Pin stop	6 Feed tube
Together with the feed tube the guide bushing guides the stud into the welding head.	The pin stop defines the stud length which is weldable.	Together with the guide bushing the feed tube guides the stud into the welding head.
		 
Order No. Guide bushing	Order No. Pin stop	Order No. Feed tube
		Automatic Manual
84-41-301	84-40-408	84-40-201 84-40-101
84-41-301	84-40-410	84-40-201 84-40-101
84-41-301	84-40-412	84-40-201 84-40-101
84-41-301	84-40-415	84-40-201 84-40-101
84-41-302	84-40-420	84-40-202 84-40-102
84-41-302	84-40-425	84-40-202 84-40-102
84-41-303	84-40-430	84-40-203 84-40-103
Order No. Guide bushing	Order No. Pin stop	Order No. Feed tube
		Automatic Manual
84-41-302	84-40-408	84-40-202 84-40-102
84-41-302	84-40-410	84-40-202 84-40-102
84-41-302	84-40-412	84-40-202 84-40-102
84-41-302	84-40-415	84-40-202 84-40-102
84-41-303	84-40-420	84-40-203 84-40-103
84-41-303	84-40-425	84-40-203 84-40-103
84-41-304	84-40-430	84-40-204 84-40-104
Order No. Guide bushing	Order No. Pin stop	Order No. Feed tube
		Automatic Manual
84-41-303	84-40-408	84-40-203 84-40-103
84-41-303	84-40-410	84-40-203 84-40-103
84-41-303	84-40-412	84-40-203 84-40-103
84-41-303	84-40-415	84-40-203 84-40-103
84-41-304	84-40-420	84-40-204 84-40-104
84-41-304	84-40-425	84-40-204 84-40-104
84-41-305	84-40-430	84-40-205 84-40-105

Equipment				9 Plunger	
Chucks				The stud is pressed through the chuck by the plunger.	
				84-40-561 (conical short) 84-40-571 (for internal threaded studs with outside diameter 7.1 mm, 8 mm)	
for CD studs with dia. 6 mm		Welding element dia.	Order No. Chuck	Stud length	
				8 mm	
				10 mm	
				12 mm	
				15 mm	
				20 mm	
				25 mm	
				30 mm	
for CD studs with dia. 7.1 mm		Welding element dia.	Order No. Chuck	Stud length	
				10 mm	
				12 mm	
				15 mm	
				20 mm	
				25 mm	
				30 mm	
for CD studs with dia. 8 mm		Welding element dia.	Order No. Chuck	Stud length	
				10 mm	
				12 mm	
				15 mm	
				20 mm	
				25 mm	
				30 mm	

12 Guide bushing	10 Pin stop	6 Feed tube
Together with the feed tube the guide bushing guides the stud into the welding head.	The pin stop defines the stud length which is weldable.	Together with the guide bushing the feed tube guides the stud into the welding head.
		 
Order No. Guide bushing	Order No. Pin stop	Order No. Feed tube
		Automatic Manual
84-41-304	84-40-408	84-40-204 84-40-104
84-41-304	84-40-410	84-40-204 84-40-104
84-41-304	84-40-412	84-40-204 84-40-104
84-41-304	84-40-415	84-40-204 84-40-104
84-41-305	84-40-420	84-40-205 84-40-105
84-41-305	84-40-425	84-40-205 84-40-105
84-41-305	84-40-430	84-40-205 84-40-105
Order No. Guide bushing	Order No. Pin stop	Order No. Feed tube
		Automatic Manual
84-41-305	84-40-410	84-40-205 84-40-105
84-41-305	84-40-412	84-40-205 84-40-105
84-41-305	84-40-415	84-40-205 84-40-105
84-41-305	84-40-420	84-40-205 84-40-105
84-41-305	84-40-425	84-40-205 84-40-105
84-41-305	84-40-430	84-40-205 84-40-105
Order No. Guide bushing	Order No. Pin stop	Order No. Feed tube
		Automatic Manual
84-41-305	84-40-410	84-40-205 84-40-105
84-41-305	84-40-412	84-40-205 84-40-105
84-41-305	84-40-415	84-40-205 84-40-105
84-41-305	84-40-420	84-40-205 84-40-105
84-41-305	84-40-425	84-40-205 84-40-105
84-41-305	84-40-430	84-40-205 84-40-105

Equipment					9 Plunger	
Chucks					The stud is pressed through the chuck by the plunger.	
	 84-40-531 (conical short)  84-40-561 (cylindrical short)  84-40-532 (conical long)  84-40-562 (cylindrical long)					
for SC studs with dia. 3 mm	 	Welding element dia. Ø 3 mm	Order No. Chuck 84-50-003	Stud length 8 mm 10 mm 12 mm 15 mm 20 mm 25 mm 30 mm	Order No. Plunger 84-40-532 84-40-531 84-40-531 84-40-531 84-40-562 84-40-562 84-40-562	
for SC studs with dia. 4 mm	 	Welding element dia. Ø 4 mm	Order No. Chuck 84-50-004	Stud length 8 mm 10 mm 12 mm 15 mm 20 mm 25 mm 30 mm	Order No. Plunger 84-40-532 84-40-531 84-40-531 84-40-531 84-40-562 84-40-562 84-40-562	
for SC studs with dia. 5 mm	 	Welding element dia. Ø 5 mm	Order No. Chuck 84-50-005	Stud length 8 mm 10 mm 12 mm 15 mm 20 mm 25 mm 30 mm	Order No. Plunger for Threaded studs / pins Internal threaded studs 84-40-532 84-40-562 84-40-531 84-40-561 84-40-531 84-40-561 84-40-561 84-40-561 84-40-562 84-40-562 84-40-562 84-40-562 84-40-562 84-40-562	

12 Guide bushing	10 Pin stop	6 Feed tube
Together with the feed tube the guide bushing guides the stud into the welding head.	The pin stop defines the stud length which is weldable.	Together with the guide bushing the feed tube guides the stud into the welding head.
		 
Order No. Guide bushing	Order No. Pin stop	Order No. Feed tube
		Automatic Manual
84-41-301	84-40-410	84-40-201 84-40-101
84-41-301	84-40-408	84-40-201 84-40-101
84-41-301	84-40-410	84-40-201 84-40-101
84-41-301	84-40-412	84-40-201 84-40-101
84-41-302	84-40-420	84-40-202 84-40-102
84-41-302	84-40-425	84-40-202 84-40-102
84-41-303	84-40-430	84-40-203 84-40-103
Order No. Guide bushing	Order No. Pin stop	Order No. Feed tube
		Automatic Manual
84-41-302	84-40-410	84-40-202 84-40-102
84-41-302	84-40-408	84-40-202 84-40-102
84-41-302	84-40-410	84-40-202 84-40-102
84-41-302	84-40-412	84-40-202 84-40-102
84-41-303	84-40-420	84-40-203 84-40-103
84-41-303	84-40-425	84-40-203 84-40-103
84-41-304	84-40-430	84-40-204 84-40-104
Order No. Guide bushing	Order No. Pin stop	Order No. Feed tube
		Automatic Manual
84-41-303	84-40-410	84-40-203 84-40-103
84-41-303	84-40-408	84-40-203 84-40-103
84-41-303	84-40-410	84-40-203 84-40-103
84-41-303	84-40-412	84-40-203 84-40-103
84-41-304	84-40-420	84-40-204 84-40-104
84-41-304	84-40-425	84-40-204 84-40-104
84-41-305	84-40-430	84-40-205 84-40-105

Equipment				9 Plunger		
Chucks				The stud is pressed through the chuck by the plunger.		
				 84-40-561 (conical short)	 84-40-571 (for internal threaded studs with outside diameter 7.1 mm, 8 mm)	
				 84-40-562 (cylindrical long)		
for SC studs with dia. 6 mm		Welding element dia. Ø 6 mm	Order No. Chuck 84-50-006	Order No. Plunger for		
				Threaded studs / pins	Internal threaded studs	
				8 mm	84-40-562	84-40-562
				10 mm	84-40-561	84-40-561
				12 mm	84-40-561	84-40-561
				15 mm	84-40-561	84-40-561
				20 mm	84-40-562	84-40-562
				25 mm	84-40-562	84-40-562
30 mm	84-40-562	84-40-562				
for SC studs with dia. 7.1 mm		Welding element dia. Ø 7.1 mm	Order No. Chuck 84-50-071	Order No. Plunger for		
				Threaded studs / pins	Internal threaded studs	
				10 mm	84-40-561	84-40-571
				12 mm	84-40-561	84-40-571
				15 mm	84-40-561	84-50-571
				20 mm	84-40-562	--
				25 mm	84-40-562	--
				30 mm	84-40-562	--
for SC studs with dia. 8 mm		Welding element dia. Ø 8 mm	Order No. Chuck 84-50-008	Order No. Plunger for		
				Threaded studs / pins	Internal threaded studs	
				10 mm	84-40-561	84-40-571
				12 mm	84-40-561	84-40-571
				15 mm	84-40-561	84-40-571
				20 mm	84-40-561	--
				25 mm	84-40-561	--
				30 mm	84-40-561	--

12 Guide bushing	10 Pin stop	6 Feed tube
Together with the feed tube the guide bushing guides the stud into the welding head.	The pin stop defines the stud length which is weldable.	Together with the guide bushing the feed tube guides the stud into the welding head.
		 
Order No. Guide bushing	Order No. Pin stop	Order No. Feed tube
		Automatic Manual
84-41-304	84-40-410	84-40-204 84-40-104
84-41-304	84-40-408	84-40-204 84-40-104
84-41-304	84-40-410	84-40-204 84-40-104
84-41-304	84-40-412	84-40-204 84-40-104
84-41-305	84-40-420	84-40-205 84-40-105
84-41-305	84-40-425	84-40-205 84-40-105
84-41-305	84-40-430	84-40-205 84-40-105
Order No. Guide bushing	Order No. Pin stop	Order No. Feed tube
		Automatic Manual
84-41-305	84-40-408	84-40-205 84-40-105
84-41-305	84-40-410	84-40-205 84-40-105
84-41-305	84-40-412	84-40-205 84-40-105
84-41-305	84-40-420	84-40-205 84-40-105
84-41-305	84-40-425	84-40-205 84-40-105
84-41-305	84-40-430	84-40-205 84-40-105
Order No. Guide bushing	Order No. Pin stop	Order No. Feed tube
		Automatic Manual
84-41-305	84-40-408	84-40-205 84-40-105
84-41-305	84-40-410	84-40-205 84-40-105
84-41-305	84-40-412	84-40-205 84-40-105
84-41-305	84-40-420	84-40-205 84-40-105
84-41-305	84-40-425	84-40-205 84-40-105
84-41-305	84-40-430	84-40-205 84-40-105



Retaining nut	for: PAH-1 to: Fix the chuck at the welding gun
	80-40-010



Special wrench	For correct positioning of the guide bushing in the piston of the welding gun (see illustration on page 87) Incorrect positioning of the guide bushing may lead to problems during stud feeding.
	84-40-010



Pin	to: Connect the pin stop to guide bushing and plunger to piston rod
	80-10-208



Centering device PZV-3	for: PAH-1 for: Exact positioning in templates
Ø 20	94-40-021
Ø 26	94-40-026
Ø 30	94-40-030



Gas shroud PSZ	for: PAH-1 (instead of foot ring with feet) for: Welding of ARC welding elements from Ø 3 mm to 8 mm with shielding gas plastic hose, l = 4 m
	94-40-022



Standard chuck
adaptor complete

to: Use standard chucks in the automatic welding
gun

92-40-041



Retaining nut
adaptor

for: Standard chuck adaptor complete
(92-40-041)

80-40-582



Adaptor

for: Standard chuck adaptor complete
(92-40-041)

80-40-389



Foot

for: Foot ring 80-40-033

Ø 10 mm

V 80-40-032



Foot ring


for: PAH-1
to: Fix the feet at the welding gun

V 80-40-033

Equipment

for KAH 412

The equipment, which is delivered together with the welding head, consists of standard components of your choice:



Pos.	number	Description	Order-Nr.
6	1	Chuck	*)
7	1	Retaining nut	80-07-564
8	1	Guide bushing	*)
9	1	Pin Stop	*)
10	1	Plunger	*)
11	1	Slot piston	80-07-567
12	1	Support for feed tube	88-10-433
13	1	Trigger pin complete	
14	1	Feed tube	*)
15	1	Pin 2 mm	80-10-208
16	1	Socket wrench AF 15	80-40-085

*) Selection according to type and dimension of the welding element

Assortment box

Accessories for easy change of equipment for other length and diameter of welding element

for KAH 412

7

84-41-312A

Assortment box, manual

for feeding of standard studs Ø 3 to 8 mm by hand

84-42-312A

Assortment box, VBZ

for feeding of standard studs Ø 3 to 8 mm by VBZ



Equipment for KAH 412

Equipment					10 Plunger		
Chucks					The stud is pressed through the chuck by the plunger.		
							
for CD studs with dia. 3 mm		Welding element dia.	Order No. Chuck	Stud length ¹⁾		Order No. Plunger	
				from min.	to max.		
				8 mm	15 mm		84-40-531
				10 mm	20 mm		84-40-531
				12 mm	20 mm		84-40-531
				15 mm	25 mm		84-40-531
				20 mm	30 mm		84-40-561
				25 mm	35 mm		84-40-561
				30 mm	40 mm		84-40-561
				35 mm	40 mm		84-40-561
				40 mm	40 mm		84-40-561
for CD studs with dia. 4 mm		Welding element dia.	Order No. Chuck	Stud length ¹⁾		Order No. Plunger	
				from min.	to max.		
				8 mm	15 mm		84-40-531
				10 mm	20 mm		84-40-531
				12 mm	20 mm		84-40-531
				15 mm	25 mm		84-40-531
				20 mm	30 mm		84-40-561
				25 mm	35 mm		84-40-561
				30 mm	40 mm		84-40-561
				35 mm	40 mm		84-40-561
				40 mm	40 mm		84-40-561
for CD studs with dia. 5 mm		Welding element dia.	Order No. Chuck	Stud length ¹⁾		Order No. Plunger for	
				from min.	to max.	Threaded studs / pins	Intenal threaded studs
				8 mm	15 mm	84-40-531	84-40-561
				10 mm	20 mm	84-40-531	84-40-561
				12 mm	20 mm	84-40-531	84-40-561
				15 mm	25 mm	84-40-561	84-40-561
				20 mm	30 mm	84-40-561	84-40-561
				25 mm	35 mm	84-40-561	84-40-561
				30 mm	40 mm	84-40-561	84-40-561
				35 mm	40 mm	84-40-561	84-40-561
				40 mm	40 mm	84-40-561	84-40-561

¹⁾ We recommend orientating the equipment as close as possible to the min. stud length

8 Guide bushing	9 Pin stop	14 Feed tube
Together with the feed tube the guide bushing guides the stud into the welding head.	The pin stop defines the smallest possible stud length which is weldable.	Together with the guide bushing the feed tube guides the stud into the welding head.
		  
Order No. Guide bushing	Order No. Pin stop	Order No. Feed tube Automatic Automatic with steel insert Manual
80-07-761	80-07-782	80-08-161 80-08-161/TKM 80-07-801
80-07-761	80-07-783	80-08-161 80-08-161/TKM 80-07-801
80-07-761	80-07-784	80-08-161 80-08-161TKM 80-07-801
80-07-762	80-07-785	80-08-162 80-08-162/TKM 80-07-802
80-07-762	80-07-786	80-08-162 80-08-162/TKM 80-07-802
80-07-763	80-07-787	80-08-163 80-08-163/TKM 80-07-803
80-07-764	80-07-788	80-08-164 80-08-164/TKM 80-07-804
80-07-764	80-07-789	80-08-164 80-08-164/TKM 80-07-804
80-07-764	80-07-789	80-08-164 80-08-164/TKM 80-07-804
Order No. Guide bushing	Order No. Pin stop	Order No. Feed tube Automatic Automatic with steel insert Manual
80-07-762	80-07-782	80-08-162 80-08-162/TKM 80-07-802
80-07-762	80-07-783	80-08-162 80-08-162/TKM 80-07-802
80-07-762	80-07-784	80-08-162 80-08-162/TKM 80-07-802
80-07-763	80-07-785	80-08-163 80-08-163/TKM 80-07-803
80-07-763	80-07-786	80-08-163 80-08-163/TKM 80-07-803
80-07-764	80-07-787	80-08-164 80-08-164/TKM 80-07-804
80-07-764	80-07-788	80-08-164 80-08-164/TKM 80-07-804
80-07-764	80-07-789	80-08-164 80-08-164/TKM 80-07-804
80-07-764	80-07-789	80-08-164 80-08-164/TKM 80-07-804
Order No. Guide bushing	Order No. Pin stop	Order No. Feed tube Automatic Automatic with steel insert Manual
80-07-763	80-07-782	80-08-163 80-08-163/TKM 80-07-803
80-07-763	80-07-783	80-08-163 80-08-163/TKM 80-07-803
80-07-763	80-07-784	80-08-163 80-08-163/TKM 80-07-803
80-07-764	80-07-785	80-08-164 80-08-164/TKM 80-07-804
80-07-764	80-07-786	80-08-164 80-08-164/TKM 80-07-804
80-07-765	80-07-787	80-08-165 80-08-165/TKM 80-07-805
80-07-765	80-07-788	80-08-165 80-08-165/TKM 80-07-805
80-07-765	80-07-789	80-08-165 80-08-165/TKM 80-07-805
80-07-765	80-07-789	80-08-165 80-08-165/TKM 80-07-805

Equipment					10 Plunger		
Chucks					The stud is pressed through the chuck by the plunger.		
	 84-40-561 (cylindrical short) 84-40-571 (for internal threaded studs with outside diameter 7.1 mm, 8 mm)						
for CD studs with dia. 6 mm		Welding element dia. ²⁾	Order No. Chuck	Stud length ¹⁾		Order No. Plunger for	
				from min.	to max.	Threaded studs / pins	Intenal threaded studs
		Ø 6 mm	84-50-006	8 mm	15 mm	84-40-561	84-40-561
				10 mm	20 mm	84-40-561	84-40-561
				12 mm	20 mm	84-40-561	84-40-561
				15 mm	25 mm	84-40-561	84-40-561
				20 mm	30 mm	84-40-561	84-40-561
				25 mm	35 mm	84-40-561	84-40-561
				30 mm	40 mm	84-40-561	84-40-561
				35 mm	40 mm	84-40-561	84-40-561
40 mm	40 mm			84-40-561	84-40-561		
for CD studs with dia. 7.1 mm		Welding element dia.	Order No. Chuck	Stud length ¹⁾		Order No. Plunger for	
				from min.	to max.	Threaded studs / pins	Intenal threaded studs
		Ø 7.1 mm	84-50-071	10 mm	20 mm	84-40-561	84-40-571
				12 mm	20 mm	84-40-561	84-40-571
				15 mm	25 mm	84-40-561	84-50-571
				20 mm	30 mm	84-40-561	84-50-571
				25 mm	30 mm	84-40-561	84-50-571
				30 mm	40 mm	84-40-561	84-50-571
				35 mm	40 mm	84-40-561	84-50-571
				40 mm	40 mm	84-40-561	84-50-571
for CD studs with dia. 8 mm				Welding element dia.	Order No. Chuck	Stud length ¹⁾	
				from min.	to max.	Threaded studs / pins	Intenal threaded studs
		Ø 8 mm	84-50-008	10 mm	20 mm	84-40-561	84-40-571
				12 mm	20 mm	84-40-561	84-40-571
				15 mm	25 mm	84-40-561	84-40-571
				20 mm	30 mm	84-40-561	84-40-571
				25 mm	30 mm	84-40-561	84-40-571
				30 mm	40 mm	84-40-561	84-40-571
				35 mm	40 mm	84-40-561	84-40-571
				40 mm	40 mm	84-40-561	84-40-571

¹⁾ We recommend orientating the equipment as close as possible to the min. stud length.


²⁾ Ø 10 mm on request, offer after check for feasibility

8 Guide bushing	9 Pin stop	14 Feed tube
Together with the feed tube the guide bushing guides the stud into the welding head.	The pin stop defines the smallest possible stud length which is weldable.	Together with the guide bushing the feed tube guides the stud into the welding head.
		  
Order No. Guide bushing	Order No. Pin stop	Order No. Feed tube Automatic Automatic with steel insert Manual
80-07-764	80-07-782	80-08-164 80-08-164/TKM 80-07-804
80-07-764	80-07-783	80-08-164 80-08-164/TKM 80-07-804
80-07-764	80-07-784	80-08-164 80-08-164/TKM 80-07-804
80-07-765	80-07-785	80-08-165 80-08-165/TKM 80-07-805
80-07-765	80-07-786	80-08-165 80-08-165/TKM 80-07-805
80-07-765	80-07-787	80-08-165 80-08-165/TKM 80-07-805
80-07-765	80-07-788	80-08-165 80-08-165/TKM 80-07-805
80-07-765	80-07-789	80-08-165 80-08-165/TKM 80-07-805
80-07-765	80-07-789	80-08-165 80-08-165/TKM 80-07-805
Order No. Guide bushing	Order No. Pin stop	Order No. Feed tube Automatic Automatic with steel insert Manual
80-07-765	80-07-783	80-08-165 80-08-165/TKM 80-07-805
80-07-765	80-07-784	80-08-165 80-08-165/TKM 80-07-805
80-07-765	80-07-785	80-08-165 80-08-165/TKM 80-07-805
88-17-679	80-07-786	80-08-165 80-08-165/TKM 80-07-805
88-17-679	80-07-787	80-08-165 80-08-165/TKM 80-07-805
80-07-766	80-07-788	80-08-981 --- 80-07-806
80-07-766	80-07-789	80-08-981 --- 80-07-806
80-07-766	80-07-789	80-08-981 --- 80-07-806
Order No. Guide bushing	Order No. Pin stop	Order No. Feed tube Automatic Automatic with steel insert Manual
80-07-765	80-07-783	80-08-165 80-08-165/TKM 80-07-805
80-07-765	80-07-784	80-08-165 80-08-165/TKM 80-07-805
80-07-765	80-07-785	80-08-165 80-08-165/TKM 80-07-805
88-17-679	80-07-786	80-08-165 80-08-165/TKM 80-07-805
88-17-679	80-07-787	80-08-165 80-08-165/TKM 80-07-805
80-07-766	80-07-788	80-08-981 --- 80-07-806
80-07-766	80-07-789	80-08-981 --- 80-07-806
80-07-766	80-07-789	80-08-981 --- 80-07-806

Equipment					10 Plunger
Chucks					The stud is pressed through the chuck by the plunger. 84-40-531 (conical short) 84-40-561 (cylindrical short)
for SC studs with dia. 3 mm		Welding element dia.	Order No. Chuck	Stud length ¹⁾	Order No. Plunger
				from min. to max.	
				8 mm 8 mm	
				10 mm 15 mm	
				12 mm 20 mm	
				15 mm 25 mm	
				20 mm 30 mm	
				25 mm 35 mm	
				30 mm 40 mm	
				35 mm 40 mm	
				40 mm 40 mm	
for SC studs with dia. 4 mm		Welding element dia.	Order No. Chuck	Stud length ¹⁾	Order No. Plunger
				from min. to max.	
				8 mm 10 mm	
				10 mm 15 mm	
				12 mm 20 mm	
				15 mm 25 mm	
				20 mm 30 mm	
				25 mm 35 mm	
				30 mm 40 mm	
				35 mm 40 mm	
				40 mm 40 mm	
for SC studs with dia. 5 mm		Welding element dia.	Order No. Chuck	Stud length ¹⁾	Order No. Plunger for
				from min. to max.	
				8 mm 10 mm	Threaded studs / pins
				10 mm 15 mm	84-40-531 84-40-561
				12 mm 20 mm	84-40-531 84-40-561
				15 mm 25 mm	84-40-561 84-40-561
				20 mm 30 mm	84-40-561 84-40-561
				25 mm 35 mm	84-40-561 84-40-561
				30 mm 40 mm	84-40-561 84-40-561
				35 mm 40 mm	84-40-561 84-40-561
				40 mm 40 mm	84-40-561 84-40-561

¹⁾ We recommend orientating the equipment as close as possible to the min. stud length

8 Guide bushing	9 Pin stop	14 Feed tube
Together with the feed tube the guide bushing guides the stud into the welding head.	The pin stop defines the smallest possible stud length which is weldable.	Together with the guide bushing the feed tube guides the stud into the welding head.
		  
Order No. Guide bushing	Order No. Pin stop	Order No. Feed tube Automatic Automatic with steel insert Manual
80-07-761	80-07-781	80-08-161 80-08-161/TKM 80-07-801
80-07-761	80-07-782	80-08-161 80-08-161/TKM 80-07-801
80-07-761	80-07-783	80-08-161 80-08-161TKM 80-07-801
80-07-762	80-07-784	80-08-162 80-08-162/TKM 80-07-802
80-07-762	80-07-785	80-08-162 80-08-162/TKM 80-07-802
80-07-763	80-07-786	80-08-163 80-08-163/TKM 80-07-803
80-07-764	80-07-787	80-08-164 80-08-164/TKM 80-07-804
80-07-764	80-07-788	80-08-164 80-08-164/TKM 80-07-804
80-07-764	80-07-789	80-08-164 80-08-164/TKM 80-07-804
Order No. Guide bushing	Order No. Pin stop	Order No. Feed tube Automatic Automatic with steel insert Manual
80-07-762	80-07-781	80-08-162 80-08-162/TKM 80-07-802
80-07-762	80-07-782	80-08-162 80-08-162/TKM 80-07-802
80-07-762	80-07-783	80-08-162 80-08-162/TKM 80-07-802
80-07-763	80-07-784	80-08-163 80-08-163/TKM 80-07-803
80-07-763	80-07-785	80-08-163 80-08-163/TKM 80-07-803
80-07-764	80-07-786	80-08-164 80-08-164/TKM 80-07-804
80-07-764	80-07-787	80-08-164 80-08-164/TKM 80-07-804
80-07-764	80-07-788	80-08-164 80-08-164/TKM 80-07-804
80-07-764	80-07-789	80-08-164 80-08-164/TKM 80-07-804
Order No. Guide bushing	Order No. Pin stop	Order No. Feed tube Automatic Automatic with steel insert Manual
80-07-763	80-07-781	80-08-163 80-08-163/TKM 80-07-803
80-07-763	80-07-782	80-08-163 80-08-163/TKM 80-07-803
80-07-763	80-07-783	80-08-163 80-08-163/TKM 80-07-803
80-07-764	80-07-784	80-08-164 80-08-164/TKM 80-07-804
80-07-764	80-07-785	80-08-164 80-08-164/TKM 80-07-804
80-07-765	80-07-786	80-08-165 80-08-165/TKM 80-07-805
80-07-765	80-07-787	80-08-165 80-08-165/TKM 80-07-805
80-07-765	80-07-788	80-08-165 80-08-165/TKM 80-07-805
80-07-765	80-07-789	80-08-165 80-08-165/TKM 80-07-805

Equipment					10 Plunger		
Chucks					The stud is pressed through the chuck by the plunger.		
					 84-40-561 (cylindrical short) 84-40-571 (for internal threaded studs with outside diameter 7,1 mm, 8 mm)		
for SC studs with dia. 6 mm		Welding element dia. ²⁾	Order No. Chuck	Stud length ¹⁾		Order No. Plunger for	
				from min.	to max.	Threaded studs / pins	Intenal threaded studs
				8 mm	15 mm	84-40-561	84-40-561
				10 mm	20 mm	84-40-561	84-40-561
				12 mm	20 mm	84-40-561	84-40-561
				15 mm	25 mm	84-40-561	84-40-561
				20 mm	30 mm	84-40-561	84-40-561
				25 mm	35 mm	84-40-561	84-40-561
				30 mm	40 mm	84-40-561	84-40-561
				35 mm	40 mm	84-40-561	84-40-561
				40 mm	40 mm	84-40-561	84-40-561
for SC studs with dia. 7,1 mm		Welding element dia.	Order No. Chuck	Stud length ¹⁾		Order No. Plunger for	
				from min.	to max.	Threaded studs / pins	Intenal threaded studs
				10 mm	15 mm	84-40-561	84-40-571
				12 mm	20 mm	84-40-561	84-40-571
				15 mm	25 mm	84-40-561	84-50-571
				20 mm	30 mm	84-40-561	84-50-571
				25 mm	30 mm	84-40-561	84-50-571
				30 mm	40 mm	84-40-561	84-50-571
				35 mm	40 mm	84-40-561	84-50-571
				40 mm	40 mm	84-40-561	84-50-571
				for SC studs with dia. 8 mm		Welding element dia.	Order No. Chuck
from min.	to max.	Threaded studs / pins	Intenal threaded studs				
10 mm	15 mm	84-40-561	84-40-571				
12 mm	20 mm	84-40-561	84-40-571				
15 mm	25 mm	84-40-561	84-40-571				
20 mm	30 mm	84-40-561	84-40-571				
25 mm	30 mm	84-40-561	84-40-571				
30 mm	40 mm	84-40-561	84-40-571				
35 mm	40 mm	84-40-561	84-40-571				
40 mm	40 mm	84-40-561	84-40-571				

¹⁾ We recommend orientating the equipment as close as possible to the min. stud length.

²⁾ Ø 10 mm on request, offer after check for feasibility

8 Guide bushing	9 Pin stop	14 Feed tube
Together with the feed tube the guide bushing guides the stud into the welding head.	The pin stop defines the smallest possible stud length which is weldable.	Together with the guide bushing the feed tube guides the stud into the welding head.
		  
Order No. Guide bushing	Order No. Pin stop	Order No. Feed tube Automatic Automatic with steel insert Manual
80-07-764	80-07-781	80-08-164 80-08-164/TKM 80-07-804
80-07-764	80-07-782	80-08-164 80-08-164/TKM 80-07-804
80-07-764	80-07-783	80-08-164 80-08-164/TKM 80-07-804
80-07-765	80-07-784	80-08-165 80-08-165/TKM 80-07-805
80-07-765	80-07-785	80-08-165 80-08-165/TKM 80-07-805
80-07-765	80-07-786	80-08-165 80-08-165/TKM 80-07-805
80-07-765	80-07-787	80-08-165 80-08-165/TKM 80-07-805
80-07-765	80-07-788	80-08-165 80-08-165/TKM 80-07-805
80-07-765	80-07-789	80-08-165 80-08-165/TKM 80-07-805
Order No. Guide bushing	Order No. Pin stop	Order No. Feed tube Automatic Automatic with steel insert Manual
80-07-765	80-07-782	80-08-165 80-08-165/TKM 80-07-805
80-07-765	80-07-783	80-08-165 80-08-165/TKM 80-07-805
80-07-765	80-07-784	80-08-165 80-08-165/TKM 80-07-805
88-17-679	80-07-785	80-08-165 80-08-165/TKM 80-07-805
88-17-679	80-07-786	80-08-165 80-08-165/TKM 80-07-805
80-07-766	80-07-787	80-08-981 --- 80-07-806
80-07-766	80-07-788	80-08-981 --- 80-07-806
80-07-766	80-07-789	80-08-981 --- 80-07-806
Order No. Guide bushing	Order No. Pin stop	Order No. Feed tube Automatic Automatic with steel insert Manual
80-07-765	80-07-782	80-08-165 80-08-165/TKM 80-07-805
80-07-765	80-07-783	80-08-165 80-08-165/TKM 80-07-805
80-07-765	80-07-784	80-08-165 80-08-165/TKM 80-07-805
88-17-679	80-07-785	80-08-165 80-08-165/TKM 80-07-805
88-17-679	80-07-786	80-08-165 80-08-165/TKM 80-07-805
80-07-766	80-07-787	80-08-981 --- 80-07-806
80-07-766	80-07-788	80-08-981 --- 80-07-806
80-07-766	80-07-789	80-08-981 --- 80-07-806



Retaining nut	for: KAH 412 to: Fix the chuck at the welding gun
---------------	--

80-07-564



Pin	to: Screw together the pin stop to the guide bushing and the plunger to the piston rod
-----	--

80-10-208



Standard chuck adaptor complete	to: Use standard chucks in automatic welding heads
---------------------------------	--

92-40-053



Retaining nut adaptor	for: Standard chuck adaptor complete (92-40-053)
-----------------------	--

80-40-641



Adaptor	for: Standard chuck adaptor complete (92-40-053)
---------	--

80-40-389



Gas shroud	for: Welding of ARC welding elements from Ø 3 mm to 8 mm with shielding gas (to be clamped on retaining nut) plastic hose, l = 4 m
------------	---

88-10-505



Gas shroud	for: Welding of ARC welding elements from Ø 3 mm to 8 mm with shielding gas (to be screwed on welding head) plastic hose, l = 5 m
------------	--

80-07-772A




Gas shroud including grounding device	for: Welding of ARC welding elements from Ø 3 mm to 8 mm with shielding gas with grounding transfer plastic hose, l = 5 m
---------------------------------------	--

80-07-772MA



Shielding gas tube	for: Gas shroud (80-07-772A and 80-07-772MA) D = 40 mm, l = 54 mm
--------------------	--

V 80-08-178A


	Pneumatic downholder	for: KAH 412 to hold down the workpiece
	Stroke 100 mm	80-08-702
	Ground connection for pneum. downholder *)	for: KAH 412 for: pneum. downholder 80-08-702
		80-09-715
	Grounding device KAH 412, variable *)	for: KAH 412 fastening the metal sheet to be welded with direct ground transfer
		88-18-220

*) Ground cable not included in delivery. Depending on the application, length and cross-section of the ground cable must be checked.



Change over kit
complete manual

for: Studs M10/M12 or Ø 12,7 mm (1/2")
length: up to 40 mm
includes:



- Pos. 1: 80-08-539 Slot piston hardened
 - Pos. 2: 80-10-281 O-ring 11 x 2
 - Pos. 3: 80-08-540 Retaining nut
 - Pos. 4: 80-11-036 O-ring 17-1,5
 - Pos. 5: 88-10-031 Chuck
 - Pos. 7: 80-07-908 Locking pin
 - Pos. 8: 80-40-241 Pressure spring
 - Pos. 9: 80-07-909 Trigger pin
 - Pos. 11: 88-10-434 Support for feed tube
 - Pos. 13: 88-10-195 Feed tube
 - Pos. 15: 80-08-546 Tension nut 1/2"
 - Pos. 35: 80-11-117 Seeger snap ring
 - Pos. 37: 80-11-118 Seeger snap ring
- please add:
- Pos. 5: 80-08-541 Chuck M10 without flange or
88-10-031 Chuck M10 with flange or
80-08-542 Chuck M12 or
80-08-543 Chuck Ø12.7

M10 without flange

88-11-930/10 *)

M10 with flange

88-11-930 *)

M12

88-11-931 *)

Ø 12.7

88-11-932 *)

*) on request, offer after check for feasibility



Change over kit
complete VBZ

for: Studs M10
includes:
equipment as required,
depending on size of studs

on request, offer after check for feasibility

Accessories for VBZ-3



Change over kit VBZ-3 for: KAH-412, PAH-1	to:	Change to another stud-Ø for fully automatic stud feeder VBZ-3
Ø 3	V	94-43-203B
Ø 4	V	94-43-204B
Ø 5	V	94-43-205B
Ø 6	V	94-43-206B
Ø 7,1	V	94-43-271B
Ø 8	V	94-43-208B
Ø 5 Fir tree stud	V	94-43-253B
Ø 6 Fir tree stud	V	94-43-263B
Ø 10	V	94-43-210B *)
*) on request, offer after check for feasibility		




Feeding tube to
VBZ-3 with 2 tube
nozzles

for: KAH 412, PAH-1
Feeding tube l = 4 m

for:

Ø 3	80-43-303A
Ø 4	80-43-304A
Ø 5	80-43-305A
Ø 6	80-43-306A
Ø 7.1 + 8	80-43-308A
Ø 10	80-43-310A



Connecting cable
RENK-round plug
connector/RENK-
round plug connec-
tor

for: Stud welding units ARC 800, IT 1002, IT 50,
IT 90, CDM 2401, CDM 3201, CDi 1502 AT
Cable length: 4 m

92-40-032



Adaptor CDMi-I/O
Interface

for: Stud welding units CDMi 2402 and CDMi 3202
for: Connecting cable RENK-round plug connector/
RENK-round plug connector

80-70-475



Connecting cable
RENK-round plug
connector/HAR-
TING-industrial
connector

for: Stud welding units CDMi 2402 and CDMi 3202
Cable length: 4 m

88-22-290H

Pneumatic ground clamps



PMB-S
(vertical movement)

Pneumatic ground clamp including clamp, swivelling, single acting
for: installation in systems of the MPW series, in automatic systems and systems of type PC-S

90-60-011



PMB-S
(vertical movement)

Pneumatic ground clamp including clamp, swivelling, single acting
incl. sliding block
for: installation in systems of the CPW series

90-61-011




Clamp
PMB-S

for: PMB-S pneumatic clamp



Standard L 24 mm

V 80-40-078



Clamp
PMB-S

for: PMB-S pneumatic clamp



Extra long, L 34 mm

V 80-40-998



PMB-LS2
(horizontal and vertical movement)

Pneumatic ground clamp including clamp (double clamp = extra charge), linear swivelling, double acting
for: installation in systems of the MPW series, in automatic systems and systems of type PC-S

90-60-120



PMB-LS2
(horizontal and vertical movement)

Pneumatic ground clamp including clamp (double clamp = extra charge), linear swivelling, double acting
incl. sliding block
for: installation in systems of the CPW series

90-61-120




Clamp
PMB-LS2

for: PMB-LS2
pneumatic ground clamp



Standard L 19 mm

V 80-40-780




Clamp
PMB-LS2

for: PMB-LS2
pneumatic ground clamp



Special L 25 mm

V 80-05-950



Clamp
PMB-LS2

for: PMB-LS2
pneumatic ground clamp



Special L 34 mm

V 88-22-772

T-slot blocks / Zero-point stop pins




T-Slot block

for: T-slot plate
to fix the pneumatic ground clamp

for: installation in systems of the MPW series, in automatic systems and systems of type PC-S

80-08-988



Sliding block

for: T-slot plate
to fix the pneumatic ground clamp

for: installation in systems of the CPW series

88-16-974



Zero-point stop adjustable

for: T-slot plate (MPW series and PC-S)
for workpiece fixing on Y-axis

Fine adjustment ($\pm 1,5$ mm) of zero-point stops via eccentric bolt possible

88-14-417



Zero point stop

for: T-slot plate
for workpiece fixing on X-axis

88-10-688




Zero-point stop pin
Ø 8 mm

for: T-slot plate (CPW series)
for workpiece fixing
for insertion into existing bore holes in the T-slot
plate

80-11-711 Metal

80-10-1543 Ceramic



Zero-point stop

for: T-slot plate (CPW series)
for workpiece fixing
slidably mounted in the slot of the T-slot plate

88-19-527



Zero-point stop pin
Ø 8 mm
with internal thread

for: T-slot plate (CPW series)
for workpiece fixing
for insertion into fixed drill holes in T-slot work
plate

80-10-2636

Metal



Pin extractor set with
sliding hammer

for: Zero-point stops with internal thread
for easier removal of stop blocks
M3 to M10
in plastic case

80-10-2024

PBZ (pneumatic single feed unit)



Pneum. single feed unit PBZ	for: KAH-412
	for: installation in systems of the MPW series
M3	94-43-133
M4	94-43-134
M5	94-43-135
M6	94-43-136
M8	94-43-138




Pneum. single feed unit PBZ	for: KAH-412
	for: installation in automatic systems and systems of type PC-S
M3	94-43-033
M4	94-43-034
M5	94-43-035
M6	94-43-036
M8	94-43-038



Basic kit for all PBZ	for: KAH-412
	for: installation in systems of the CPW series

88-20-206



Pneum. single feed unit PBZ	for: KAH-412
	for: installation in systems of the CPW series (Basic kit 88-20-206 necessary)


M3	88-18-163
----	-----------

M4	88-18-164
----	-----------

M5	88-18-165
----	-----------

M6	88-18-166
----	-----------

M8	88-18-168
----	-----------



Changeover kit PBZ-U for: KAH 412	to: Change into another stud-Ø on the PBZ (single studfeeding)
	for: installation in systems of the MPW series, the CPW series, in automatic systems and systems of type PC-S

M3	94-43-103
----	-----------


M4	94-43-104
----	-----------

M5	94-43-105
----	-----------

M6	94-43-106
----	-----------

M8	94-43-108
----	-----------


Further components



Pneumatic stud feeding switch PBW complete

for: Feeding studs with the same diameter but different lengths into one automatic welding head
for: installation in systems of the MPW series

M3	88-15-5811B
M4	88-15-5812B
M5	88-15-5813B
M6	88-15-5814B
M8	88-15-5815B



Pneumatic stud feeding switch PBW complete

for: Feeding studs with the same diameter but different lengths into one automatic welding head
for: installation in automatic systems


M3	80-08-0471B
M4	80-08-0472B
M5	80-08-0473B
M6	80-08-0474B
M8	80-08-0475B



Holder for all PBW

Holder and mounting hardware
for: installation in systems of the CPW series

88-17-698



Pneumatic stud feeding switch PBW complete

for: Feeding studs with the same diameter but different lengths into one automatic welding head
for: installation in systems of the CPW series (Holder PBW 88-17-698 necessary)

M3	88-18-173
M4	88-18-174
M5	88-18-175
M6	88-18-176
M8	88-18-178



Solenoid valve complete with utensil socket

for: switching the compressed air for manual stud feeding or for closing/opening the ground clamp

88-25-857



Solenoid valve

for: switching the compressed air for manual stud feeding or for closing/opening the ground clamp

80-10-188



Utensil socket

for: Solenoid valve 80-10-188

80-10-189



Ring initiator

to: See if stud has been fed

hole-Ø	
10 mm	80-50-0083
20 mm	80-50-491

	Coupling ring initiator	for: Connection between ring initiator and CNC control
		80-10-375
	ESS External weld start	for: HBS power units with 7-pin-plug
		90-70-016
	Connecting line complete for welding head KAH 412 continuously	for: CDM 2401, CDM 3201, CDMi 2402, CDMi 3202, ARC 500 AT, ARC 800 AT, ARC 1550 AT, IT 1001 AT, IT 1002 AT
	3 m, 25 mm ²	92-40-131
	5 m, 35 mm ²	92-40-130
	SSS Welding current sensor	for: Signal output - welding current was active incl. connection cable (5 m)
		90-70-020
	Working stroke complete, with height adjustment (125/45 mm) without ring initiator	for: KAH 412 to: Move the welding head to the welding position
		80-09-760



Working stroke complete, with height adjustment (125/45 mm) **with** ring initiator


for: KAH 412
to: Move the welding head to the welding position

80-09-750



Data cable

for: Connection for RS232 interface
CDMi 2402 and CDMi 3202
cable length 3 m




80-50-1243




Adaptor

for: CDMi-I/O interface
CDMi 2402 and CDMi 3202
Interface connections for VBZ-3, external welding start and contact sleeve



80-70-475



Panel cover, lockable

for: CDMi 2402 and CDMi 3202
Protection against unintended entries on display

88-21-811A



Data cable

for: Connection for RS232 interface
IT 50, IT 90, IT 130, IT 1002 (Autom.)
cable length 3 m

80-70-308

Accessories for MPW





Adjustment set for welding head position

for: KAH 412
for setting the welding head after a welding head change or as a quality measure to ensure the accuracy of the stud welding machines type MPW and TKM 2

88-22-301B



Code Reader

incl. software package
for: for calling up welding programs via barcode in the control system of stud welding machines type MPW and TKM 2

88-21-127



RDS Software

for: MPW series
for: Error analysis in the MPW control

80-50-2011

Coupling types	Page
	132

Extension cables and adaptors	Page
	133

Ground cables	Page
	134 - 135

Cable socket:

Cable plugs:

Mini
BKM 25

10 - 25 mm²

Mini
SKM 25

Standard

BK 25
BK 50

16 - 25 mm²
35 - 50 mm²

Standard

SK 25
SK 50

Pegasar 500 accu,
Pegasar 500 accu Insulation
CDi 1502, CDi 2302, CDi 3102

C 06-3

C08, CA 08, PAH-1 ¹⁾
CI 03

Pegasar 500 accu Insulation
ARC 500, ARC 800
Visar 650

CA 08, A 12, A 16, AI 06
A 12

ARC 1550

CA 08, A 12, A 16, A 22, AI 06, PAH-1 ¹⁾

IT 1002

CA 08, A 12, A 16, AI 06, PAH-1 ¹⁾, AM 12 A, AM 12 W

CDMi 2402, CDMi 3202

C 08, CA 08, PAH-1

SC 2401

AI 06

IT 50

A 12, A 16, AI 06, PAH-1

Ground cable 92-40-154

Ground cable 92-40-095
Ground cable 92-40-091 (ISO)
Ground cable 92-40-091 (ISO)

Ground cable 93-40-020
Ground cable 93-40-020

Ground cable 93-40-013

Ground cable 93-40-020

Ground cable 92-40-095

Ground cable 92-40-078 (ISO)

Ground cable 93-40-020

BK 70

50 - 70 mm²

SK 70

IT 2002

A 12, A 16, A 22,
A 25 with adaptor 88-16-760

Ground cable 93-40-019 (1 vg) ²⁾
(for welding elements to M20)

IT 90

A 12, A 16, A 22, PAH-1,
A 25 with adaptor 88-16-760

Ground cable 93-40-019 (1 vg) ²⁾
(for welding elements to M20)

Plus (with double clamp screws)

BKK 70
BKK 95

50 - 70 mm²
70 - 95 mm²

Plus (with double clamp screws)

SKK 70
SKK 95

IT 2002, IT 130

A 12, A 16, A 22,
A 25 with adaptor 88-16-760

Ground cable 93-40-072
(for welding elements to M22)

IT 90

A 12, A 16, A 22, PAH-1,
A 25 with adaptor 88-16-760

Ground cable 93-40-072
(for welding elements to M22)

Special (with double clamp screws)

BKS 95
BKS 120

70 - 95 mm²
95 - 120 mm²

Special (with double clamp screws)

SKS 95
SKS 120

IT 2002, IT 90, IT 130

A 25

Ground cable 93-40-080 with adap-
tor 88-16-760

IT 3002

AI 06, A 12, A 16 und A 22 with adaptor 93-40-120, A 25

Ground cable 93-40-080
Extension cable 93-40-078

¹⁾ only for automatic version

²⁾ Ground cable with one vice grip (vg), 2 ground cables are necessary



Extension cable ARC (50-mm ² -male) (50-mm ² -cable)	for:	welding guns A 12, A 16 (SK 50)
	for:	stud welding with ceramic ferrule or shielding gas
	5 m	93-40-030
	10 m	93-40-023
	25 m	93-40-025



Extension cable ARC (95-mm ² -male) (95-mm ² -cable)	for:	welding gun A 22 (SKK 95)
	5 m	93-40-035
	10 m	93-40-064
	25 m	93-40-032

	Ground cable for CD (50-mm²-male) (25-mm²-cable)	for: Pegasar 500 accu, Pegasar 500 accu Insulation, CDi 502, (for CD ISO nails) SK 50
2.5 m (1 Vice grip 10")	92-40-154	
	Ground cable for CD (50-mm²-male) (25-mm²-cable)	for: CD series, CDi series, CDM series, CDMi series SK 50
2.5 m (2 Vice grips 10")	92-40-095	
	Ground cable for ARC (50-mm²-male) (25-mm²-cable)	for: ARC 500, ARC 800, IT 50, IT 1001, IT 1002, Visar 650, Visar 1200 SK 50
5 m (2 Vice grips 10")	93-40-020	
	Ground cable for ARC (70-mm²-male) (70-mm²-cable)	for: IT 90, IT 130, IT 2001, IT 2002 (2 pieces required) (for welding elements to M20) SK 70
5 m (1 Vice grip 10")	93-40-019	




Ground cable
for ARC
(95-mm²-male)
(95-mm²-cable)

for: IT 90, IT 130, IT 2001, IT 2002
(2 pieces required)
(for welding elements to M22)
SKK 95

5 m (1 Vice grip 10")

93-40-072



Ground cable
for ISO
(50-mm²-male)
(16-mm²-cable)

for: CD 1501, CDi 1502, CDi 502,
Pegasar 500 accu Insulation
(for cupped head pins)
SK 50

6.7 m (1 Vice grip 10")

92-40-091

Bending device	Page
	138
Torque bending test device	Page
	138
Automatic center punch	Page
	138
Socket wrench	Page
	139

Quickboy / Bench mounting unit / Mobility systems	Page
	139

Protective hose	Page
	139

Welding agent	Page
	140

Metaflux	Page
	140



Bending device complete, including bushings 3 - 8 mm	for: Bending test according to DIN EN ISO 14555 including equipment to eject stuck studs
--	--

92-40-042



Bending device without bushings	for: Bending test according to DIN EN ISO 14555 including equipment to eject stuck studs
---------------------------------	--

80-40-120



Bushing	for: Bending device
---------	---------------------

for stud M3 80-40-121

for stud M4 80-40-122

for stud M5 80-40-123

for stud M6 80-40-124

for stud M8 80-40-125



Torque bending test device	for: Non-destructive test method. Torque check of the welded studs for quality assurance
----------------------------	--

92-40-135A



Automatic center punch	for: Defined punched holes
------------------------	----------------------------

80-10-353



Socket wrench	to: Change the chuck
for:	
C 08/CA 08/AI 06	80-40-085 (AF 17)
ACCU-TWIN	80-41-032 (AF 13)



Quickboy	
for C 08/CA 08	92-40-142
for PAH-1	92-40-140



Bench mounting unit	for: C 08
	92-40-100



IT Mobility System*)	for: IT 50, IT 90, IT 130
	Organisation system – Particularly well-suited for transporting the complete welding system incl. gas cylinder, stud welding gun and accessories
	*) Not in stock, order-related production, Price excl. stud welding unit, gas cylinder and accessories Modification done at HBS
	88-21-510



Protective hose, complete with zipper	to:	Protect cables from dirt, dust and welding sparks
230 cm	80-11-230	for: CA 08, PAH-1
430 cm	80-11-430	for A 12, A 12-FL (5m cable)



Wetting agent, silicon free	to:	Reduce the adherences of welding sparks to the equipment of the welding gun or the welding head
	89-10-100	



Metaflux Multi-TS spray bottle 500 ml	to:	Reduce the adherences of welding sparks to the workpiece surface
	80-10-1914	



Metaflux Multi-TS spray 10 l	to:	Reduce the adherences of welding sparks to the workpiece surface
	80-10-1623	

Which stud welding unit / which welding gun is best for my task?


To be clearly defined prior to purchase

WHAT – what purpose is the stud to serve?

HOW – which stud welding process is to be used?

ONTO WHAT – onto what is welding to be performed?

The purpose determines the technical equipment.



Our device technology is, of course, completely – from in-house development to production –

MADE & DESIGNED IN GERMANY




Contact us for an individual consultation or browse through our extensive [Stud Welding Systems Catalogue](#).



Which welding element is best for my task?

The welding element is a decisive factor for a good welding quality. In addition to our extensive portfolio of standard welding elements based on DIN ISO 13918, HBS also offers you a number of industry-specific welding elements, e.g., from the area of automation or isolation.



Our particular strength lies in the development of custom-made welding elements that are optimally tailored to the respective application.



Contact us for an individual consultation or browse through our extensive [Welding Elements Catalogue](#).





Leading through Technology, Quality and Service

Accessories Catalogue